



#### RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS										
Sample Status				ABNORMAL	NORMAL					
Silicon	ppm	ASTM D5185m	>15	<u> </u>	14					

Customer Id: SDITER Sample No.: PCA0101556 Lab Number: 05937404 Test Package: PLANT



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Don Baldridge +1 <u>don.b505@comcast.net</u>

*To change component or sample information:* Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u> There are no recommended actions for this sample.

#### **HISTORICAL DIAGNOSIS**

#### 22 Sep 2022 Diag: Jonathan Hester

NORMAL



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





## **OIL ANALYSIS REPORT**

Sample Rating Trend

# DIRT

Machine Id **CRANE 14** Component

# Main Hoist

PETRO CANADA ENDURATEX EP 220 (--- GAL)

### DIAGNOSIS

#### A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

Elemental level of silicon (Si) above normal.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFOR		method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0101556	PCA0077457	
Sample Date		Client Info		28 Aug 2023	22 Sep 2022	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	Not Changd	
Sample Status				ABNORMAL	NORMAL	
WEAR METAL	S	method	limit/base	current	history1	history2
PQ		ASTM D8184		16	7	
Iron	ppm	ASTM D5185m	>20	4	3	
Chromium	ppm	ASTM D5185m	>20	0	0	
Nickel	ppm	ASTM D5185m		<1	0	
Titanium	ppm	ASTM D5185m	20	0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum		ASTM D5185m	>20	0	0	
Lead	ppm ppm	ASTM D5185m		0 <1	0	
		ASTM D5185m	>20	<1	0	
Copper Tin	ppm	ASTM D5185m		<1	0	
Vanadium	ppm	ASTM D5185m	20	0	0	
	ppm			0	0	
Cadmium	ppm	ASTM D5185m		U	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	60	14	12	
Barium	ppm	ASTM D5185m	0	15	12	
Molybdenum	ppm	ASTM D5185m	0	<1	<1	
Manganese	ppm	ASTM D5185m	0	0	0	
Vagnesium	ppm	ASTM D5185m	0	1	0	
Calcium	ppm	ASTM D5185m	0	13	11	
Phosphorus	ppm	ASTM D5185m	270	176	171	
Zinc	ppm	ASTM D5185m	0	8	6	
Sulfur	ppm	ASTM D5185m	11200	9315	9957	
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<u> </u>	14	
Sodium	ppm	ASTM D5185m		0	0	
Potassium	ppm	ASTM D5185m	>20	<1	0	
FLUID DEGRAI	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.40	0.36	0.35	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	VLITE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	LIGHT	VLITE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
Free Water	scalar	*Visual		NEG	ocation BRAD B	LLIS - SDITER
						Page 3 of 4



# **OIL ANALYSIS REPORT**

