


# OIL ANALYSIS REPORT

**Sample Rating Trend**

**NORMAL**

 Machine Id  
**121642-5088**

 Component  
**Diesel Engine**

 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**
**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

**Wear**

All component wear rates are normal.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0019370</b>	PCA0098011	---
Sample Date	Client Info			<b>25 Aug 2023</b>	08 Jun 2023	---
Machine Age	mls	Client Info		<b>0</b>	18907	---
Oil Age	mls	Client Info		<b>0</b>	0	---
Oil Changed	Client Info			<b>N/A</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>70</b>	102	---
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	3	---
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	<1	---
Titanium	ppm	ASTM D5185m		<b>0</b>	0	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>20	<b>13</b>	22	---
Lead	ppm	ASTM D5185m	>40	<b>1</b>	3	---
Copper	ppm	ASTM D5185m	>330	<b>60</b>	218	---
Tin	ppm	ASTM D5185m	>15	<b>3</b>	6	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>17</b>	55	---
Barium	ppm	ASTM D5185m	0	<b>0</b>	<1	---
Molybdenum	ppm	ASTM D5185m	50	<b>52</b>	37	---
Manganese	ppm	ASTM D5185m	0	<b>2</b>	3	---
Magnesium	ppm	ASTM D5185m	950	<b>746</b>	450	---
Calcium	ppm	ASTM D5185m	1050	<b>1574</b>	1221	---
Phosphorus	ppm	ASTM D5185m	995	<b>953</b>	997	---
Zinc	ppm	ASTM D5185m	1180	<b>1269</b>	1306	---
Sulfur	ppm	ASTM D5185m	2600	<b>3158</b>	3459	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>14</b>	31	---
Sodium	ppm	ASTM D5185m		<b>3</b>	3	---
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	5	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>1.4</b>	0.8	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>12.4</b>	9.8	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>24.6</b>	22.9	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>23.4</b>	21.4	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>8.1</b>	6.3	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>12.7</b>	10.7	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0019370 **Received** : 30 Aug 2023  
**Lab Number** : **05938614** **Diagnosed** : 31 Aug 2023  
**Unique Number** : 10629226 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #119**  
 39 INDUSTRIAL AVE  
 HASBROUCK HEIGHTS, NJ  
 US 07604  
 Contact: MIKE LONGETTE  
 mlongette@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (201)528-7053