


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
631553

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0019366	PCA0098033	PCA0094286
Sample Date	Client Info		24 Aug 2023	05 May 2023	24 Mar 2023
Machine Age	mls	Client Info	83003	63181	55974
Oil Age	mls	Client Info	0	0	0
Oil Changed	Client Info		Not Changed	Changed	Not Changed
Sample Status			NORMAL	ATTENTION	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	45	95	84
Chromium	ppm	ASTM D5185m >20	3	7	6
Nickel	ppm	ASTM D5185m >4	<1	2	2
Titanium	ppm	ASTM D5185m	0	<1	0
Silver	ppm	ASTM D5185m >3	<1	0	0
Aluminum	ppm	ASTM D5185m >20	30	71	75
Lead	ppm	ASTM D5185m >40	0	3	3
Copper	ppm	ASTM D5185m >330	93	249	232
Tin	ppm	ASTM D5185m >15	4	14	13
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	11	19	19
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 50	62	55	48
Manganese	ppm	ASTM D5185m 0	2	5	5
Magnesium	ppm	ASTM D5185m 950	889	651	658
Calcium	ppm	ASTM D5185m 1050	1298	1710	1687
Phosphorus	ppm	ASTM D5185m 995	967	780	727
Zinc	ppm	ASTM D5185m 1180	1252	991	1046
Sulfur	ppm	ASTM D5185m 2600	2819	1853	1762

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	6	10	10
Sodium	ppm	ASTM D5185m	2	6	5
Potassium	ppm	ASTM D5185m >20	63	183	162




INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.8	1.1	1
Nitration	Abs/cm	*ASTM D7624 >20	9.6	13.1	12.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	20.2	24.7	23.3

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	17.2	26.5	24.0
Base Number (BN)	mg KOH/g	ASTM D2896	7.3	6.7	6.6









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	▲ 14.5	10.6

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0019366 **Received** : 30 Aug 2023
Lab Number : 05938654 **Diagnosed** : 31 Aug 2023
Unique Number : 10629266 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #119
 39 INDUSTRIAL AVE
 HASBROUCK HEIGHTS, NJ
 US 07604
 Contact: MIKE LONGETTE
 mlongette@millertransgroup.com
 T:
 F: (201)528-7053

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)