


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 10651 Component

Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

668 (GAL)		Sep2022 No	v2022 Jan2023 Feb20	23 Mar2023 Apr2023 May20	123 Aug202:	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0091374	GFL0088796	GFL0082864
Sample Date		Client Info		28 Aug 2023	02 Aug 2023	17 May 2023
Machine Age	hrs	Client Info		20006	19849	19369
Oil Age	hrs	Client Info		928	1937	1457
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METAL	_S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	45	51	71
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	7	8	19
Lead	ppm	ASTM D5185m	>50	2	3	11
Copper	ppm	ASTM D5185m	>225	3	4	11
Tin	ppm	ASTM D5185m	>10	<1	<1	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		82	108	112
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		1	2	2
Calcium	ppm	ASTM D5185m		123	124	137
Phosphorus	ppm	ASTM D5185m		230	226	291
Zinc	ppm	ASTM D5185m		9	16	4
Sulfur	ppm	ASTM D5185m		2114	1929	1976
CONTAMINAN	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	6	7	6
Sodium	ppm	ASTM D5185m		2	<1	2
Potassium	ppm	ASTM D5185m	>20	1	<1	1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	ERTIES	method	limit/base	current	history1	history2
	-					




OIL ANALYSIS REPORT





SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS



Non-ferrous Metals









Laboratory Sample No. Lab Number

: GFL0091374 : 05939400 Unique Number : 10630012 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 30 Aug 2023 Diagnosed

: 01 Sep 2023 Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge

1280 Rum Creek Parkway Stockbridge, GA US 30281

Contact: JOSHUA TINKER

joshuatinker@gflenv.com T:

Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL010 [WUSCAR] 05939400 (Generated: 09/01/2023 21:02:52) Rev: 1

F: