


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



Machine Id **728007** 

Component

**Transmission (Auto)** 

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

# DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the


## **Fluid Condition**

The condition of the oil is acceptable for the time in service.

68 ( GAL)		Jan 2023	Mar2023 May2023	May2023 Jul2023	Aug2023	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0091452	GFL0088752	GFL008611
Sample Date		Client Info		28 Aug 2023	16 Aug 2023	12 Jul 2023
Machine Age	hrs	Client Info		11617	11450	11327
Oil Age	hrs	Client Info		1065	898	1913
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR META	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	43	43	53
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	<1	0
Aluminum	ppm	ASTM D5185m	>50	30	28	34
Lead	ppm	ASTM D5185m	>50	2	3	2
Copper	ppm	ASTM D5185m	>225	24	27	32
Tin	ppm	ASTM D5185m	>10	1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		86	90	69
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m		0	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		2	2	<1
Calcium	ppm	ASTM D5185m		107	112	108
Phosphorus	ppm	ASTM D5185m		235	227	248
Zinc	ppm	ASTM D5185m		<1	9	<1
Sulfur	ppm	ASTM D5185m		1837	1601	1817
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	7	7	7
Sodium	ppm	ASTM D5185m		2	0	1
Potassium	ppm	ASTM D5185m	>20	1	2	2
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPI	ERTIES	method	limit/base	current	history1	history2
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	- 01	AOTA DA45	0.4	20.0	00.0	00.0





# **OIL ANALYSIS REPORT**




SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

## **GRAPHS**











Laboratory Sample No. Lab Number

Unique Number : 10630019 Test Package : FLEET

: GFL0091452 : 05939407

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 30 Aug 2023 Received Diagnosed : 01 Sep 2023 Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge

1280 Rum Creek Parkway Stockbridge, GA US 30281

Contact: TECHNICIAN ACCOUNT

wcgfldemo@gmail.com T:

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: