




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**928040**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

| method        | limit/base  | current            | history1    | history2    |
|---------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info | <b>GFL0089489</b>  | GFL0078774  | GFL0058685  |
| Sample Date   | Client Info | <b>19 Jul 2023</b> | 10 May 2023 | 31 Jan 2023 |
| Machine Age   | hrs         | <b>5044</b>        | 4460        | 3030        |
| Oil Age       | hrs         | <b>0</b>           | 0           | 0           |
| Oil Changed   | Client Info | <b>Changed</b>     | Changed     | Changed     |
| Sample Status |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

## CONTAMINATION

| method | limit/base   | current        | history1 | history2 |
|--------|--------------|----------------|----------|----------|
| Fuel   | WC Method >5 | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Glycol | WC Method    | <b>NEG</b>     | NEG      | NEG      |

## WEAR METALS

| method   | limit/base           | current      | history1 | history2 |
|----------|----------------------|--------------|----------|----------|
| Iron     | ppm ASTM D5185m >110 | <b>5</b>     | 5        | 9        |
| Chromium | ppm ASTM D5185m >4   | <b>&lt;1</b> | <1       | <1       |
| Nickel   | ppm ASTM D5185m >2   | <b>0</b>     | 0        | 0        |
| Titanium | ppm ASTM D5185m      | <b>0</b>     | 0        | 0        |
| Silver   | ppm ASTM D5185m >2   | <b>0</b>     | 0        | 0        |
| Aluminum | ppm ASTM D5185m >25  | <b>&lt;1</b> | <1       | 2        |
| Lead     | ppm ASTM D5185m >45  | <b>0</b>     | 0        | 0        |
| Copper   | ppm ASTM D5185m >85  | <b>&lt;1</b> | <1       | <1       |
| Tin      | ppm ASTM D5185m >4   | <b>0</b>     | 0        | 0        |
| Vanadium | ppm ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |
| Cadmium  | ppm ASTM D5185m      | <b>0</b>     | 0        | 0        |

## ADDITIVES

| method     | limit/base           | current      | history1 | history2 |
|------------|----------------------|--------------|----------|----------|
| Boron      | ppm ASTM D5185m 0    | <b>0</b>     | 2        | 2        |
| Barium     | ppm ASTM D5185m 0    | <b>0</b>     | 0        | 0        |
| Molybdenum | ppm ASTM D5185m 60   | <b>66</b>    | 60       | 61       |
| Manganese  | ppm ASTM D5185m 0    | <b>&lt;1</b> | <1       | <1       |
| Magnesium  | ppm ASTM D5185m 1010 | <b>1060</b>  | 1013     | 955      |
| Calcium    | ppm ASTM D5185m 1070 | <b>1164</b>  | 1098     | 1091     |
| Phosphorus | ppm ASTM D5185m 1150 | <b>1110</b>  | 1065     | 996      |
| Zinc       | ppm ASTM D5185m 1270 | <b>1320</b>  | 1333     | 1221     |
| Sulfur     | ppm ASTM D5185m 2060 | <b>3816</b>  | 3824     | 3459     |

## CONTAMINANTS

| method    | limit/base          | current  | history1 | history2 |
|-----------|---------------------|----------|----------|----------|
| Silicon   | ppm ASTM D5185m >30 | <b>2</b> | 2        | 3        |
| Sodium    | ppm ASTM D5185m     | <b>2</b> | <1       | 1        |
| Potassium | ppm ASTM D5185m >20 | <b>0</b> | 1        | <1       |

## INFRA-RED



| method    | limit/base               | current     | history1 | history2 |
|-----------|--------------------------|-------------|----------|----------|
| Soot %    | % *ASTM D7844 >3         | <b>0.3</b>  | 0.3      | 0.4      |
| Nitration | Abs/cm *ASTM D7624 >20   | <b>7.9</b>  | 7.9      | 8.8      |
| Sulfation | Abs/.1mm *ASTM D7415 >30 | <b>17.7</b> | 19.1     | 18.9     |

## FLUID DEGRADATION

| method           | limit/base               | current     | history1 | history2 |
|------------------|--------------------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm *ASTM D7414 >25 | <b>13.7</b> | 15.3     | 15.3     |
| Base Number (BN) | mg KOH/g ASTM D2896 9.8  | <b>8.4</b>  | 8.7      | 8.3      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1    | history2 |      |
|------------------|--------|------------|---------|-------------|----------|------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | <b>13.4</b> | 13.7     | 13.4 |

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0089489 **Received** : 05 Sep 2023  
**Lab Number** : **05941767** **Diagnosed** : 05 Sep 2023  
**Unique Number** : 10632379 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 918 - Hartland HC**  
 630 E Industrial Drive  
 Hartland, WI  
 US 53029  
 Contact: David McCall  
 david.mccall@gflenv.com  
 T: (262)369-3069  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)