




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
10712

Component
Diesel Engine

Fluid
CHEVRON DELO 400 SDE SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0083134	GFL0083108	GFL05898313
Sample Date	Client Info	31 Aug 2023	17 Jul 2023	10 Jul 2023
Machine Age	hrs	Client Info	0	0
Oil Age	hrs	Client Info	0	0
Oil Changed	Client Info	Not Changed	Not Changed	Not Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	51	4	4
Chromium	ppm ASTM D5185m >4	3	<1	<1
Nickel	ppm ASTM D5185m >2	2	0	<1
Titanium	ppm ASTM D5185m	<1	0	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >25	6	2	2
Lead	ppm ASTM D5185m >45	<1	0	0
Copper	ppm ASTM D5185m >85	3	0	<1
Tin	ppm ASTM D5185m >4	<1	0	0
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	22	12	2
Barium	ppm ASTM D5185m	0	0	2
Molybdenum	ppm ASTM D5185m	56	59	61
Manganese	ppm ASTM D5185m	<1	0	0
Magnesium	ppm ASTM D5185m	729	924	916
Calcium	ppm ASTM D5185m	1465	1275	1101
Phosphorus	ppm ASTM D5185m 760	842	1016	1028
Zinc	ppm ASTM D5185m 800	1055	1231	1239
Sulfur	ppm ASTM D5185m 3000	2999	3681	3466

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	13	3	3
Sodium	ppm ASTM D5185m	14	2	<1
Potassium	ppm ASTM D5185m >20	<1	<1	2

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	1.4	0	0.1
Nitration	Abs/cm *ASTM D7624 >20	8.9	6.2	5.4
Sulfation	Abs/.1mm *ASTM D7415 >30	20.5	17.9	18.1

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.5	14.1	13.6
Base Number (BN)	mg KOH/g ASTM D2896 10	8.0	8.5	9.9







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.6	13.8	13.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0083134
Lab Number : 05943286
Unique Number : 10633898
Test Package : FLEET

GFL Environmental - 074 - Douglas - Transwaste
 1219 Landfill Road
 Douglas, GA
 US 31533
 Contact: CURTIS JACOBS
 CURTIS.JACOBS@GFLENV.COM
 T: (912)384-6001
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)