


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 10629

Component
Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

668 (GAL)		Jan 2023	Feb2023 Mar2023	May2023 Jul2023	Sep 2023	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0091410	GFL0086102	GFL0086137
Sample Date		Client Info		01 Sep 2023	27 Jul 2023	10 Jul 2023
Machine Age	hrs	Client Info		1400	30823	1158
Oil Age	hrs	Client Info		838	1850	1717
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METAI	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	43	40	38
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	6	4	4
Lead	ppm	ASTM D5185m	>50	0	<1	1
Copper	ppm	ASTM D5185m	>225	6	4	4
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		70	91	81
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		2	0	0
Calcium	ppm	ASTM D5185m		128	127	134
Phosphorus	ppm	ASTM D5185m		225	222	226
Zinc	ppm	ASTM D5185m		2	0	0
Sulfur		ASTM D5185m		1998	2018	2102
	ppm		lii+/l			
CONTAMINA	VIS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	4	5
Sodium	ppm	ASTM D5185m		4	2	3
Potassium	ppm	ASTM D5185m	>20	<1	<1	2
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPI	ERTIES	method	limit/base	current	history1	history2

Visc @ 40°C

cSt


ASTM D445 34

32.6

33.0





OIL ANALYSIS REPORT






GRAPHS











Laboratory Sample No. Lab Number Unique Number : 10634619 Test Package : FLEET

: GFL0091410 : 05944007

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 06 Sep 2023 Diagnosed : 08 Sep 2023 Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge 1280 Rum Creek Parkway

Stockbridge, GA US 30281

Contact: TECHNICIAN ACCOUNT

wcgfldemo@gmail.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: