




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**729105**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0086934</b>	GFL0087004	GFL0069282
Sample Date	Client Info		<b>07 Sep 2023</b>	29 Jun 2023	07 Jun 2023
Machine Age	hrs	Client Info	<b>22113</b>	21690	21560
Oil Age	hrs	Client Info	<b>500</b>	600	300
Oil Changed	Client Info		<b>Not Changed</b>	Changed	Not Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>3</b>	10	22
Chromium	ppm	ASTM D5185m >4	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m >2	<b>0</b>	<1	3
Titanium	ppm	ASTM D5185m	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	1
Aluminum	ppm	ASTM D5185m >25	<b>&lt;1</b>	<1	2
Lead	ppm	ASTM D5185m >45	<b>&lt;1</b>	2	<1
Copper	ppm	ASTM D5185m >85	<b>0</b>	<1	▲ 82
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	2
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>5</b>	2	42
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	2
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	59	84
Manganese	ppm	ASTM D5185m 0	<b>0</b>	<1	2
Magnesium	ppm	ASTM D5185m 1010	<b>1016</b>	895	846
Calcium	ppm	ASTM D5185m 1070	<b>1159</b>	1043	1182
Phosphorus	ppm	ASTM D5185m 1150	<b>1046</b>	971	956
Zinc	ppm	ASTM D5185m 1270	<b>1272</b>	1176	1131
Sulfur	ppm	ASTM D5185m 2060	<b>3796</b>	3001	2960

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>4</b>	3	21
Sodium	ppm	ASTM D5185m	<b>&lt;1</b>	5	0
Potassium	ppm	ASTM D5185m >20	<b>0</b>	1	3

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.1</b>	0.5	0.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>4.6</b>	7.8	8.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>16.9</b>	19.8	21.4

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>12.5</b>	15.0	18.1
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>9.3</b>	8.8	7.3







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.1</b>	12.8	12.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0086934 **Received** : 13 Sep 2023  
**Lab Number** : **05949793** **Diagnosed** : 15 Sep 2023  
**Unique Number** : 10645752 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 408 - Brown City**  
 4235 M-53  
 BROWN CITY, MI  
 US 48416  
 Contact: WILLIAM DEOLA  
 bdeola@gflenv.com  
 T: (810)238-2836  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)