




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**228077**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0086867</b>	GFL0072553	GFL0068315
Sample Date	Client Info	<b>07 Sep 2023</b>	12 Jul 2023	20 Jun 2023
Machine Age	hrs	<b>23670</b>	600	0
Oil Age	hrs	<b>600</b>	600	0
Oil Changed	Client Info	<b>Changed</b>	Changed	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>6</b>	17	10
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	2	2
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm ASTM D5185m >2	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >2	<b>0</b>	0	<1
Aluminum	ppm ASTM D5185m >25	<b>&lt;1</b>	<1	1
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>1</b>	3	1
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	0
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>6</b>	6	8
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>61</b>	67	59
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>1028</b>	1070	983
Calcium	ppm ASTM D5185m 1070	<b>1180</b>	1232	1122
Phosphorus	ppm ASTM D5185m 1150	<b>1069</b>	1103	1063
Zinc	ppm ASTM D5185m 1270	<b>1299</b>	1328	1310
Sulfur	ppm ASTM D5185m 2060	<b>3843</b>	3740	3739

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	4	4
Sodium	ppm ASTM D5185m	<b>2</b>	16	2
Potassium	ppm ASTM D5185m >20	<b>&lt;1</b>	0	1

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.1</b>	0.2	0.2
Nitration	Abs/cm *ASTM D7624 >20	<b>5.9</b>	7.2	6.7
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>16.8</b>	18.7	18.9

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>12.6</b>	15.0	14.8
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.8</b>	9.4	9.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.5	13.5

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0086867 **Received** : 13 Sep 2023  
**Lab Number** : **05949837** **Diagnosed** : 15 Sep 2023  
**Unique Number** : 10645796 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 419 - Metro Saginaw**  
 6950 N Michigan  
 Saginaw, MI  
 US 48604  
 Contact: Jeremy Hines  
 jhines@gflenv.com  
 T: (800)684-1277  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)