




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
711038

Component
Diesel Engine

Fluid
PETRO CANADA 15W40 (5 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0088543	GFL0083300	GFL0083288
Sample Date	Client Info	13 Sep 2023	29 Jun 2023	20 Jun 2023
Machine Age	hrs	652	652	652
Oil Age	hrs	452	320	516
Oil Changed	Client Info	N/A	N/A	N/A
Sample Status		NORMAL	NORMAL	ABNORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	▲ 2.7

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >90	25	29	84
Chromium	ppm ASTM D5185m >20	<1	<1	2
Nickel	ppm ASTM D5185m >2	0	0	0
Titanium	ppm ASTM D5185m >2	0	<1	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >20	<1	1	6
Lead	ppm ASTM D5185m >40	0	0	0
Copper	ppm ASTM D5185m >330	5	11	19
Tin	ppm ASTM D5185m >15	<1	0	<1
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	3	0	29
Barium	ppm ASTM D5185m	0	14	3
Molybdenum	ppm ASTM D5185m	61	54	50
Manganese	ppm ASTM D5185m	<1	<1	7
Magnesium	ppm ASTM D5185m	1015	849	852
Calcium	ppm ASTM D5185m	1198	942	1218
Phosphorus	ppm ASTM D5185m	1063	878	696
Zinc	ppm ASTM D5185m	1327	1138	877
Sulfur	ppm ASTM D5185m	3670	3019	2579

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	4	3	14
Sodium	ppm ASTM D5185m	8	11	5
Potassium	ppm ASTM D5185m >20	14	21	11
Glycol	% *ASTM D2982	NEG	0.0	NEG

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.5	0.6	1.2
Nitration	Abs/cm *ASTM D7624 >20	9.2	9.9	14.0
Sulfation	Abs/.1mm *ASTM D7415 >30	19.7	21.4	26.9

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	16.5	18.9	28.2
Base Number (BN)	mg KOH/g ASTM D2896	8.0	8.0	5.9







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.0	14.0	▲ 12.2

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0088543 **Received** : 13 Sep 2023
Lab Number : 05950004 **Diagnosed** : 18 Sep 2023
Unique Number : 10645963 **Diagnostician** : Don Baldrige
Test Package : FLEET (Additional Tests: Glycol)

GFL Environmental - 017 - Durham
 148 Stone Park Court
 Durham, NC
 US 27703
 Contact: Shane Parks
 shane.parks@gflenv.com
 T: (919)596-1363
 F: (919)598-1852

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)