




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**3402M**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0092935</b>	GFL0055936	GFL0067558
Sample Date	Client Info		<b>12 Sep 2023</b>	23 Jun 2023	30 May 2023
Machine Age	hrs	Client Info	<b>18134</b>	17775	17600
Oil Age	hrs	Client Info	<b>17775</b>	589	599
Oil Changed	Client Info		<b>N/A</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>15</b>	16	11
Chromium	ppm	ASTM D5185m >4	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m >25	<b>2</b>	2	4
Lead	ppm	ASTM D5185m >45	<b>2</b>	<1	<1
Copper	ppm	ASTM D5185m >85	<b>4</b>	2	1
Tin	ppm	ASTM D5185m >4	<b>2</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>1</b>	2	5
Barium	ppm	ASTM D5185m 0	<b>44</b>	<1	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	62	61
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>917</b>	946	954
Calcium	ppm	ASTM D5185m 1070	<b>1007</b>	1101	1106
Phosphorus	ppm	ASTM D5185m 1150	<b>955</b>	1016	1067
Zinc	ppm	ASTM D5185m 1270	<b>1183</b>	1246	1322
Sulfur	ppm	ASTM D5185m 2060	<b>3085</b>	3624	3480

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>5</b>	13	12
Sodium	ppm	ASTM D5185m	<b>5</b>	3	2
Potassium	ppm	ASTM D5185m >20	<b>2</b>	2	3

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.7</b>	0.3	0.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.5</b>	8.0	6.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.4</b>	19.0	18.4

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.8</b>	15.2	14.3
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.8</b>	9.5	9.3







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.7	13.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0092935 **Received** : 15 Sep 2023  
**Lab Number** : 05952526 **Diagnosed** : 18 Sep 2023  
**Unique Number** : 10648485 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 463 - Cheboygan**  
 501 N. Western Ave  
 Cheboygan, MI  
 US 49721  
 Contact: Chris Gee  
 cgee@gflenv.com  
 T: (231)597-8553  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)