




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**511022**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0092938</b>	GFL0015802	GFL0067610
Sample Date	Client Info		<b>12 Sep 2023</b>	28 Jun 2023	13 Mar 2023
Machine Age	hrs	Client Info	<b>2612</b>	2259	1891
Oil Age	hrs	Client Info	<b>1891</b>	1891	598
Oil Changed	Client Info		<b>N/A</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>24</b>	17	39
Chromium	ppm	ASTM D5185m >20	<b>1</b>	2	1
Nickel	ppm	ASTM D5185m >5	<b>6</b>	6	▲ 17
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	2	0
Silver	ppm	ASTM D5185m >2	<b>&lt;1</b>	2	<1
Aluminum	ppm	ASTM D5185m >20	<b>5</b>	4	7
Lead	ppm	ASTM D5185m >40	<b>3</b>	6	<1
Copper	ppm	ASTM D5185m >330	<b>44</b>	41	109
Tin	ppm	ASTM D5185m >15	<b>3</b>	3	3
Vanadium	ppm	ASTM D5185m	<b>0</b>	1	0
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	2	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	3
Barium	ppm	ASTM D5185m 0	<b>44</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	59	57
Manganese	ppm	ASTM D5185m 0	<b>2</b>	3	2
Magnesium	ppm	ASTM D5185m 1010	<b>916</b>	978	850
Calcium	ppm	ASTM D5185m 1070	<b>1036</b>	1149	1125
Phosphorus	ppm	ASTM D5185m 1150	<b>886</b>	980	810
Zinc	ppm	ASTM D5185m 1270	<b>1164</b>	1250	1028
Sulfur	ppm	ASTM D5185m 2060	<b>2624</b>	3305	2394

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>8</b>	8	9
Sodium	ppm	ASTM D5185m	<b>2</b>	4	3
Potassium	ppm	ASTM D5185m >20	<b>16</b>	11	20

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.6</b>	0.5	0.7
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.6</b>	8.7	11.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.8</b>	20.4	22.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.5</b>	16.0	18.1
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.1</b>	8.0	6.1








# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.5	13.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0092938 **Received** : 15 Sep 2023  
**Lab Number** : **05952539** **Diagnosed** : 18 Sep 2023  
**Unique Number** : 10648498 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 463 - Cheboygan**  
 501 N. Western Ave  
 Cheboygan, MI  
 US 49721  
 Contact: Chris Gee  
 cgee@gflenv.com  
 T: (231)597-8553  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)