




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**913180**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0094941</b>	GFL0088402	GFL0070062
Sample Date	Client Info		<b>13 Sep 2023</b>	15 Aug 2023	24 May 2023
Machine Age	hrs	Client Info	<b>1114</b>	962	467
Oil Age	hrs	Client Info	<b>962</b>	467	297
Oil Changed	Client Info		<b>Not Chngd</b>	Diff Oil	Not Chngd
Sample Status			<b>NORMAL</b>	NORMAL	ATTENTION

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>8</b>	17	32
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>0</b>	<1	1
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	1	1
Aluminum	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	4
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m >330	<b>3</b>	19	79
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	1	4
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>&lt;1</b>	8	215
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	6
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	63	110
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	4
Magnesium	ppm	ASTM D5185m 1010	<b>1043</b>	925	650
Calcium	ppm	ASTM D5185m 1070	<b>1201</b>	1150	1208
Phosphorus	ppm	ASTM D5185m 1150	<b>1077</b>	968	646
Zinc	ppm	ASTM D5185m 1270	<b>1331</b>	1190	768
Sulfur	ppm	ASTM D5185m 2060	<b>3977</b>	3358	2301

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	10	72
Sodium	ppm	ASTM D5185m	<b>2</b>	6	2
Potassium	ppm	ASTM D5185m >20	<b>2</b>	2	6

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.2</b>	0.4	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>6.5</b>	7.5	9.4
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.2</b>	20.1	24.0

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>13.7</b>	15.7	20.0
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.1</b>	7.5	8.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.2	13.3 ▲ 10.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0094941 **Received** : 15 Sep 2023  
**Lab Number** : 05953316 **Diagnosed** : 19 Sep 2023  
**Unique Number** : 10649275 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 084 - Clarksville**  
 699 Jack Miller Boulevard  
 Clarksville, TN  
 US 37042  
 Contact: Destin Love

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
 F: (931)553-0641