


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **423044-35**

Component **Diesel Engine**

DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Dec2021 Apr2022 Aug2022 Jan2023 Mar2023 Jun2023 Jun2023 Smp2023							
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0087893	GFL0081161	GFL0081166	
Sample Date		Client Info		12 Sep 2023	27 Jun 2023	01 Jun 2023	
Machine Age	hrs	Client Info		59129	58973	58925	
Oil Age	hrs	Client Info		600	600	600	
Oil Changed		Client Info		Not Changd	Changed	Not Changd	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>2.0	<1.0	<1.0	<1.0	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	.S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	5	10	9	
Chromium	ppm	ASTM D5185m	>20	<1	<1	0	
Nickel	ppm	ASTM D5185m	>4	<1	0	0	
Titanium	ppm	ASTM D5185m		0	<1	0	
Silver	ppm	ASTM D5185m	>3	1	0	0	
Aluminum	ppm	ASTM D5185m	>20	2	0	1	
Lead	ppm	ASTM D5185m	>40	<1	<1	0	
Copper	ppm	ASTM D5185m	>330	<1	<1	<1	
Tin	ppm	ASTM D5185m	>15	0	<1	0	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		<1	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	250	18	129	137	
Barium	ppm	ASTM D5185m	10	2	0	0	
Molybdenum	ppm	ASTM D5185m	100	65	69	69	
Manganese	ppm	ASTM D5185m		<1	<1	0	
Magnesium	ppm	ASTM D5185m	450	939	776	815	
Calcium	ppm	ASTM D5185m	3000	1148	1122	1240	
Phosphorus	ppm	ASTM D5185m	1150	1078	1033	1055	
Zinc	ppm	ASTM D5185m	1350	1280	1209	1275	
Sulfur	ppm	ASTM D5185m	4250	3596	3352	3894	
CONTAMINAN	ITS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	3	4	4	
Sodium	ppm	ASTM D5185m	>158	<1	0	2	
Potassium	ppm	ASTM D5185m	>20	<1	<1	<1	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.2	0.3	0.2	
Nitration	Abs/cm	*ASTM D7624	>20	5.0	5.2	5.7	
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.0	19.3	18.9	
FLUID DEGRA	DATION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.7	15.1	13.9	
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	9.1	8.4	8.8	



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	RHES	metnoa	ilmit/base	current	nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	14.4	13.6	13.3	13.3

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10654973 Test Package : FLEET

: GFL0087893 : 05953760

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 18 Sep 2023 : 20 Sep 2023 Diagnostician : Don Baldridge GFL Environmental - 166 - Phenix City

18 Old Brickyard Rd Phenix City, AL US 36869

Contact: DEAN PEACE JR dean.peace@gflenv.com

T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: