


PROBLEM SUMMARY

Sample Rating Trend



VIS DEBRIS



Machine Id
2026878
 Component
Rear Differential
 Fluid
NOT GIVEN (--- QTS)

COMPONENT CONDITION SUMMARY

No relevant graphs to display

RECOMMENDATION

No corrective action is recommended at this time.
Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS

Sample Status				ABNORMAL	---	---
Debris	scalar	*Visual	NONE	▲ MODER	---	---

Customer Id: PERLEWNC
Sample No.: PCA0103989
Lab Number: 05954354
Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:
 Jonathan Hester +1 919-379-4092 x4092
jhester@wearcheckusa.com

To change component or sample information:
 Customer Service +1 1-800-237-1369
customerservice@wearcheck.com


RECOMMENDED ACTIONS

There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

OIL ANALYSIS REPORT

Sample Rating Trend



VIS DEBRIS



Machine Id
2026878
 Component
Rear Differential
 Fluid
NOT GIVEN (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0103989	---	---
Sample Date	Client Info	13 Sep 2023	---	---
Machine Age	mls	Client Info	314875	---
Oil Age	mls	Client Info	314875	---
Oil Changed	Client Info	Not Chngd	---	---
Sample Status		ABNORMAL	---	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	153	---
Chromium	ppm	ASTM D5185m >10	1	---
Nickel	ppm	ASTM D5185m >10	5	---
Titanium	ppm	ASTM D5185m	<1	---
Silver	ppm	ASTM D5185m	0	---
Aluminum	ppm	ASTM D5185m >25	4	---
Lead	ppm	ASTM D5185m >25	<1	---
Copper	ppm	ASTM D5185m >100	2	---
Tin	ppm	ASTM D5185m >10	<1	---
Vanadium	ppm	ASTM D5185m	<1	---
Cadmium	ppm	ASTM D5185m	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	300	---
Barium	ppm	ASTM D5185m	0	---
Molybdenum	ppm	ASTM D5185m	<1	---
Manganese	ppm	ASTM D5185m	12	---
Magnesium	ppm	ASTM D5185m	0	---
Calcium	ppm	ASTM D5185m	7	---
Phosphorus	ppm	ASTM D5185m	1378	---
Zinc	ppm	ASTM D5185m	0	---
Sulfur	ppm	ASTM D5185m	25056	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >75	37	---
Sodium	ppm	ASTM D5185m	8	---
Potassium	ppm	ASTM D5185m >20	3	---


VISUAL

method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	NONE	---
Yellow Metal	scalar	*Visual NONE	NONE	---
Precipitate	scalar	*Visual NONE	NONE	---
Silt	scalar	*Visual NONE	NONE	---
Debris	scalar	*Visual NONE	▲ MODER	---
Sand/Dirt	scalar	*Visual NONE	NONE	---
Appearance	scalar	*Visual NORML	NORML	---
Odor	scalar	*Visual NORML	NORML	---
Emulsified Water	scalar	*Visual >.2	NEG	---
Free Water	scalar	*Visual	NEG	---

FLUID PROPERTIES




method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	104	---

OIL ANALYSIS REPORT



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0103989 **Received** : 18 Sep 2023
Lab Number : **05954354** **Diagnosed** : 20 Sep 2023
Unique Number : 10655567 **Diagnostician** : Jonathan Hester
Test Package : FLEET

PERDUE FARMS - Lewiston
 210 GRIFFINS QUARTER RD
 LEWISTON, NC
 US 27849
 Contact: NELSON WALLACE
 nelson.wallace2@perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: