


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**738606**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (--- GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0105300</b>	PCA0093248	PCA0090119
Sample Date	Client Info		<b>01 Sep 2023</b>	22 Feb 2023	10 Feb 2023
Machine Age	mls	Client Info	<b>191794</b>	40502	160000
Oil Age	mls	Client Info	<b>191794</b>	40502	0
Oil Changed	Client Info		<b>Changed</b>	Changed	N/A
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

### CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

### WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>93</b>	66	▲ 129
Chromium	ppm	ASTM D5185m >20	<b>4</b>	3	5
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	1
Titanium	ppm	ASTM D5185m	<b>9</b>	26	5
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m >20	<b>17</b>	20	41
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	<1
Copper	ppm	ASTM D5185m >330	<b>29</b>	60	50
Tin	ppm	ASTM D5185m >15	<b>2</b>	2	2
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

### ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>3</b>	18	3
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>62</b>	39	61
Manganese	ppm	ASTM D5185m 0	<b>2</b>	2	2
Magnesium	ppm	ASTM D5185m 950	<b>921</b>	635	891
Calcium	ppm	ASTM D5185m 1050	<b>1400</b>	1508	1425
Phosphorus	ppm	ASTM D5185m 995	<b>1082</b>	903	928
Zinc	ppm	ASTM D5185m 1180	<b>1367</b>	1122	1204
Sulfur	ppm	ASTM D5185m 2600	<b>2965</b>	2507	2206

### CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>9</b>	8	10
Sodium	ppm	ASTM D5185m	<b>2</b>	<1	4
Potassium	ppm	ASTM D5185m >20	<b>32</b>	50	98



### INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1.8</b>	1.3	2.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>14.6</b>	12.0	20.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>27.3</b>	25.0	33.2

### FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>27.2</b>	24.7	40.5
Base Number (BN)	mg KOH/g	ASTM D2896	<b>4.7</b>	6.3	▲ 2.9









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>12.1</b>	11.4	12.9

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0105300 **Received** : 19 Sep 2023  
**Lab Number** : 05955152 **Diagnosed** : 21 Sep 2023  
**Unique Number** : 10656365 **Diagnostician** : Don Baldrige  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #118**  
 2196 BENNETT ROAD  
 PHILADELPHIA, PA  
 US 19116  
 Contact: ROSTY VITER  
 rviter@millertransgroup.com  
 T: (215)552-9832  
 F: (215)552-9892

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)