


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
738214
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0102920	PCA0100768	PCA0076767
Sample Date	Client Info		07 Sep 2023	21 Jun 2023	03 Nov 2022
Machine Age	mls	Client Info	169010	144109	59173
Oil Age	mls	Client Info	109837	144109	59173
Oil Changed	Client Info		Not Chngd	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	32	73	124
Chromium	ppm	ASTM D5185m >20	2	3	6
Nickel	ppm	ASTM D5185m >4	<1	<1	0
Titanium	ppm	ASTM D5185m	6	24	<1
Silver	ppm	ASTM D5185m >3	<1	<1	3
Aluminum	ppm	ASTM D5185m >20	14	37	80
Lead	ppm	ASTM D5185m >40	<1	0	<1
Copper	ppm	ASTM D5185m >330	23	44	316
Tin	ppm	ASTM D5185m >15	<1	2	5
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	6	15	17
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 50	63	46	49
Manganese	ppm	ASTM D5185m 0	<1	2	4
Magnesium	ppm	ASTM D5185m 950	911	736	535
Calcium	ppm	ASTM D5185m 1050	1298	1531	1805
Phosphorus	ppm	ASTM D5185m 995	1059	900	741
Zinc	ppm	ASTM D5185m 1180	1283	1171	958
Sulfur	ppm	ASTM D5185m 2600	3317	2985	2376

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	6	9	11
Sodium	ppm	ASTM D5185m	<1	4	4
Potassium	ppm	ASTM D5185m >20	28	83	193



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.8	1.7	1.5
Nitration	Abs/cm	*ASTM D7624 >20	8.5	13.5	16.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	20.0	27.5	28.4

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	15.6	24.6	33.3
Base Number (BN)	mg KOH/g	ASTM D2896	7.8	6.0	6.1









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	10.9	11.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0102920 **Received** : 19 Sep 2023
Lab Number : 05955160 **Diagnosed** : 20 Sep 2023
Unique Number : 10656373 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #118
 2196 BENNETT ROAD
 PHILADELPHIA, PA
 US 19116
 Contact: ROSTY VITER
 rviter@millertransgroup.com
 T: (215)552-9832
 F: (215)552-9892

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)