




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**825026-178**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0090920</b>	GFL0062007	GFL0061976
Sample Date	Client Info		<b>14 Sep 2023</b>	30 Jun 2023	04 Jan 2023
Machine Age	hrs	Client Info	<b>20422</b>	19908	18096
Oil Age	hrs	Client Info	<b>514</b>	600	399
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	SEVERE

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	0.4
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>9</b>	12	42
Chromium	ppm	ASTM D5185m >20	<b>0</b>	<1	1
Nickel	ppm	ASTM D5185m >5	<b>2</b>	1	2
Titanium	ppm	ASTM D5185m >2	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	5
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	2
Copper	ppm	ASTM D5185m >330	<b>&lt;1</b>	2	12
Tin	ppm	ASTM D5185m >15	<b>1</b>	2	6
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>5</b>	15	33
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>64</b>	63	62
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	4
Magnesium	ppm	ASTM D5185m 1010	<b>1042</b>	964	381
Calcium	ppm	ASTM D5185m 1070	<b>1175</b>	1132	2176
Phosphorus	ppm	ASTM D5185m 1150	<b>1022</b>	1020	1085
Zinc	ppm	ASTM D5185m 1270	<b>1332</b>	1338	1370
Sulfur	ppm	ASTM D5185m 2060	<b>3208</b>	3241	3599

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	7	104
Sodium	ppm	ASTM D5185m	<b>5</b>	5	12
Potassium	ppm	ASTM D5185m >20	<b>2</b>	<1	10

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.3</b>	0.4	0.5
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.9</b>	9.0	10.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.0</b>	22.0	24.9

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.0</b>	18.6	21.7
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>6.9</b>	6.8	4.4







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.6 ▲ 12.15

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0090920 **Received** : 21 Sep 2023  
**Lab Number** : 05957446 **Diagnosed** : 22 Sep 2023  
**Unique Number** : 10658659 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 656 - Culpeper Hauling**  
 15490 Montanus Drive  
 Culpeper, VA  
 US 22701  
 Contact: Matt Hanna  
 mhanna@gflenv.com  
 T: (540)727-0887  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)