

# **OIL ANALYSIS REPORT**





710011 Component **Diesel Engine** 

PETRO CANADA DURON SHP 15W40 (25 GAL)

## DIAGNOSIS Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the


### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

N SHP 15W40 (2	5 GAL)		0ct2022	Sep 2023			
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0085004	GFL0052076		
Sample Date		Client Info		18 Sep 2023	17 Oct 2022		
Machine Age	hrs	Client Info		10790	7845		
Oil Age	hrs	Client Info		10790	7845		
Oil Changed		Client Info		N/A	N/A		
Sample Status				NORMAL	NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>3.0	<1.0	<1.0		
Glycol		WC Method		NEG	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2	
Iron		ASTM D5185m	>120	41	6		
Chromium	ppm	ASTM D5185m	>20	2	<1		
Nickel	ppm	ASTM D5185m	>5	<1	0		
Titanium	ppm	ASTM D5185m	>2	0	<1		
Silver		ASTM D5185m	>2	0	0		
Aluminum	ppm	ASTM D5185m	>20	8	1		
Lead		ASTM D5185m	>40	0	0		
	ppm	ASTM D5185m	>330	<1	<1		
Copper Tin	ppm	ASTM D5185m	>15	<1	0		
Vanadium	ppm	ASTM D5185m	>10	0	<1		
Cadmium		ASTM D5185m		0	0		
	ppm						
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	3	0		
Barium	ppm	ASTM D5185m	0	0	0		
Molybdenum	ppm	ASTM D5185m	60	65	54		
Manganese	ppm	ASTM D5185m	0	<1	<1		
Magnesium	ppm	ASTM D5185m	1010	1072	915		
Calcium	ppm	ASTM D5185m	1070	1213	1064		
Phosphorus	ppm	ASTM D5185m	1150	1179	942		
Zinc	ppm	ASTM D5185m	1270	1456	1242		
Sulfur	ppm	ASTM D5185m	2060	4037	3210		
CONTAMINAN	TS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	5	2		
Sodium	ppm	ASTM D5185m		7	3		
Potassium	ppm	ASTM D5185m	>20	3	3		
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>4	0.8	0.3		
Nitration	Abs/cm	*ASTM D7624	>20	10.6	8.5		
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.8	20.4		
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.6	17.0		
Oxidation Base Number (BN)	Abs/.1mm mg KOH/g	*ASTM D7414 ASTM D2896		17.6 8.0	17.0 9.4		




## **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	


FLUID PROPI	ERHES	method			history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.4	13.8	

### **GRAPHS**













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10659684 Test Package : FLEET

: GFL0085004 : 05958471

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 22 Sep 2023 Diagnosed : 22 Sep 2023 Diagnostician : Wes Davis

GFL Environmental - 410 - Michigan West 39000 Van Born Rd

Wayne, MI US 48184 Contact: Belal Dgheish bdgheish@gflenv.com T: (734)714-2340

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)