


OIL ANALYSIS REPORT

Machine Id **425160** Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)				Aug2023		
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0093025		
Sample Date		Client Info		25 Aug 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINA	ΓΙΟΝ	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Glycol		WC Method		NEG		
WEAR METAI	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	22		
Chromium	ppm	ASTM D5185m		<1		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m		0		
Lead	ppm	ASTM D5185m	>40	0		
Copper	ppm	ASTM D5185m		3		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m	>10	0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES	ррпі	method	limit/base		history1	history2
				current	,	HISTOLYZ
Boron	ppm	ASTM D5185m	0	32		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	60	58		
Manganese	ppm	ASTM D5185m	0	<1		
Magnesium	ppm	ASTM D5185m	1010	889		
Calcium	ppm	ASTM D5185m	1070	1386		
Phosphorus	ppm	ASTM D5185m	1150	971		
Zinc	ppm	ASTM D5185m	1270	1191		
Sulfur	ppm	ASTM D5185m	2060	3785		
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	4		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3		
Nitration	Abs/cm	*ASTM D7624	>20	6.5		
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.5		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.3		
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	9.2		




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
	DTIEO	and the section of	1224/1		la facta a more	la la da un O


FLUID FROFI		method			HISTOLAL	HISTOLYZ
Visc @ 100°C	cSt	ASTM D445	15.4	13.2		

GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10659709 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0093025 : 05958496

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Received Diagnosed Diagnostician : Wes Davis

: 22 Sep 2023 : 23 Sep 2023 GFL Environmental - 413 - Whiteland Hauling 2959 S EMERSON AVE

WHITELAND, IN US 46184

Contact: Christyan Trent-Proctor

ctrentproctor@gflenv.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: