

# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**G. LOPES CONSTRUCTION INC./ON-ROAD**  
 Machine Id  
**358**  
 Component  
**Transmission**  
 Fluid  
**PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)**



## DIAGNOSIS

**Recommendation**  
 Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

**Wear**  
 All component wear rates are normal.

**Contamination**  
 There is no indication of any contamination in the fluid.

**Fluid Condition**  
 The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0104685</b>	---	---
Sample Date	Client Info	<b>20 Sep 2023</b>	---	---
Machine Age	hrs Client Info	<b>75000</b>	---	---
Oil Age	hrs Client Info	<b>75000</b>	---	---
Oil Changed	Client Info	<b>N/A</b>	---	---
Sample Status		<b>NORMAL</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron ppm	ASTM D5185m >200	<b>79</b>	---	---
Chromium ppm	ASTM D5185m >10	<b>0</b>	---	---
Nickel ppm	ASTM D5185m	<b>0</b>	---	---
Titanium ppm	ASTM D5185m	<b>0</b>	---	---
Silver ppm	ASTM D5185m	<b>0</b>	---	---
Aluminum ppm	ASTM D5185m >50	<b>45</b>	---	---
Lead ppm	ASTM D5185m >50	<b>7</b>	---	---
Copper ppm	ASTM D5185m >200	<b>11</b>	---	---
Tin ppm	ASTM D5185m >10	<b>5</b>	---	---
Vanadium ppm	ASTM D5185m	<b>0</b>	---	---
Cadmium ppm	ASTM D5185m	<b>0</b>	---	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron ppm	ASTM D5185m	<b>94</b>	---	---
Barium ppm	ASTM D5185m	<b>0</b>	---	---
Molybdenum ppm	ASTM D5185m	<b>0</b>	---	---
Manganese ppm	ASTM D5185m	<b>1</b>	---	---
Magnesium ppm	ASTM D5185m	<b>2</b>	---	---
Calcium ppm	ASTM D5185m	<b>76</b>	---	---
Phosphorus ppm	ASTM D5185m	<b>265</b>	---	---
Zinc ppm	ASTM D5185m	<b>0</b>	---	---
Sulfur ppm	ASTM D5185m	<b>1383</b>	---	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm	ASTM D5185m >50	<b>8</b>	---	---
Sodium ppm	ASTM D5185m	<b>6</b>	---	---
Potassium ppm	ASTM D5185m >20	<b>6</b>	---	---



## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g	ASTM D8045	<b>1.06</b>	---	---

## VISUAL

method	limit/base	current	history1	history2
White Metal scalar	*Visual NONE	<b>NONE</b>	---	---
Yellow Metal scalar	*Visual NONE	<b>NONE</b>	---	---
Precipitate scalar	*Visual NONE	<b>NONE</b>	---	---
Silt scalar	*Visual NONE	<b>NONE</b>	---	---
Debris scalar	*Visual NONE	<b>NONE</b>	---	---
Sand/Dirt scalar	*Visual NONE	<b>NONE</b>	---	---
Appearance scalar	*Visual NORML	<b>NORML</b>	---	---
Odor scalar	*Visual NORML	<b>NORML</b>	---	---
Emulsified Water scalar	*Visual >0.1	<b>NEG</b>	---	---
Free Water scalar	*Visual	<b>NEG</b>	---	---









# OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	34	<b>33.9</b>	---	---

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0104685 **Received** : 22 Sep 2023  
**Lab Number** : 05958718 **Diagnosed** : 24 Sep 2023  
**Unique Number** : 10659931 **Diagnostician** : Wes Davis  
**Test Package** : MOB 2

**G LOPES CONSTRUCTION**  
 565 WINTHROP ST  
 TAUNTON, MA  
 US 02780  
 Contact: BUTCH MCGRATH  
 bmcgrath@glopes.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: