


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
FORD 615 (S/N 1FAHPZMK8JG117474)
 Component
Gasoline Engine
 Fluid
PETRO CANADA SUPREME 5W20 MOTOR OIL (6 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	PCA0100398	PCA0100380	PCA0097961	
Sample Date	Client Info	31 Aug 2023	31 Jul 2023	02 Jun 2023	
Machine Age	mls	Client Info	58449	57389	55208
Oil Age	mls	Client Info	1060	2181	1859
Oil Changed	Client Info	Changed	Changed	Changed	
Sample Status		NORMAL	NORMAL	NORMAL	

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >4.0	<1.0	<1.0	<1.0
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >150	3	5	4
Chromium	ppm ASTM D5185m >20	0	<1	<1
Nickel	ppm ASTM D5185m >5	0	<1	0
Titanium	ppm ASTM D5185m	<1	0	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >40	<1	2	<1
Lead	ppm ASTM D5185m >50	<1	<1	0
Copper	ppm ASTM D5185m >155	<1	2	2
Tin	ppm ASTM D5185m >10	<1	0	0
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 183	84	35	53
Barium	ppm ASTM D5185m 0	0	2	0
Molybdenum	ppm ASTM D5185m 36	66	62	61
Manganese	ppm ASTM D5185m 0	<1	<1	<1
Magnesium	ppm ASTM D5185m 417	565	438	488
Calcium	ppm ASTM D5185m 1318	1278	1260	1279
Phosphorus	ppm ASTM D5185m 773	728	670	724
Zinc	ppm ASTM D5185m 845	904	804	874
Sulfur	ppm ASTM D5185m 2690	3045	2696	3283

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	16	21	22
Sodium	ppm ASTM D5185m >400	3	7	5
Potassium	ppm ASTM D5185m >20	2	<1	1



INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	0	0	0
Nitration	Abs/cm *ASTM D7624 >20	7.5	9.0	7.8
Sulfation	Abs/.1mm *ASTM D7415 >30	17.2	19.8	19.5

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	12.6	15.6	14.5
Base Number (BN)	mg KOH/g ASTM D2896 6.5	5.8	4.6	4.7









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	8.42	8.5	8.4	8.6

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0100398 **Received** : 02 Oct 2023
Lab Number : 05965903 **Diagnosed** : 02 Oct 2023
Unique Number : 10672454 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

VILLAGE OF NORTH RIVERSIDE
 2345 S DESPLAINES
 NORTH RIVERSIDE, IL
 US 60546
 Contact: Service Manager
 vznrdpw@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: