




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id

**2485**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	<b>GFL0068131</b>	GFL0068157	GFL0046521	
Sample Date	Client Info	<b>25 Sep 2023</b>	05 Apr 2023	12 Sep 2022	
Machine Age	hrs	Client Info	<b>790</b>	675	583
Oil Age	hrs	Client Info	<b>600</b>	600	600
Oil Changed	Client Info	<b>Changed</b>	Changed	Changed	
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL	

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>10</b>	2	0
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >4	<b>&lt;1</b>	0	<1
Titanium	ppm ASTM D5185m	<b>0</b>	<1	<1
Silver	ppm ASTM D5185m >3	<b>1</b>	0	1
Aluminum	ppm ASTM D5185m >20	<b>8</b>	0	<1
Lead	ppm ASTM D5185m >40	<b>0</b>	0	0
Copper	ppm ASTM D5185m >330	<b>74</b>	<1	<1
Tin	ppm ASTM D5185m >15	<b>1</b>	0	1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>11</b>	26	86
Barium	ppm ASTM D5185m 0	<b>0</b>	0	<1
Molybdenum	ppm ASTM D5185m 60	<b>65</b>	58	66
Manganese	ppm ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>968</b>	826	823
Calcium	ppm ASTM D5185m 1070	<b>1154</b>	1062	1120
Phosphorus	ppm ASTM D5185m 1150	<b>1076</b>	965	923
Zinc	ppm ASTM D5185m 1270	<b>1355</b>	1113	1109
Sulfur	ppm ASTM D5185m 2060	<b>3006</b>	2742	2849

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>8</b>	4	3
Sodium	ppm ASTM D5185m	<b>3</b>	<1	0
Potassium	ppm ASTM D5185m >20	<b>14</b>	1	0

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.3</b>	0.1	0.1
Nitration	Abs/cm *ASTM D7624 >20	<b>7.6</b>	4.6	5.3
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.0</b>	16.8	19.0

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.1</b>	11.6	13.6
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.2</b>	9.1	10.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.0</b>	12.5	12.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0068131 **Received** : 04 Oct 2023  
**Lab Number** : **05968626** **Diagnosed** : 04 Oct 2023  
**Unique Number** : 10675177 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 028 - Weldon**  
 2211 US Highway 301  
 Halifax, NC  
 US 27839  
 Contact: TRAVIS PORCH  
 tporch@gflenv.com  
 T: (252)532-3344  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)