




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

2636

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0075172	GFL0061895	GFL0061889
Sample Date	Client Info	03 Oct 2023	30 Jun 2023	12 Jun 2023
Machine Age	hrs	20488	19878	19727
Oil Age	hrs	20488	19878	19727
Oil Changed	Client Info	Changed	Not Changd	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m >165	1	4	3
Chromium	ppm	ASTM D5185m >5	<1	2	0
Nickel	ppm	ASTM D5185m >4	0	1	0
Titanium	ppm	ASTM D5185m >2	0	2	0
Silver	ppm	ASTM D5185m >2	0	2	0
Aluminum	ppm	ASTM D5185m >20	2	2	0
Lead	ppm	ASTM D5185m >150	0	4	0
Copper	ppm	ASTM D5185m >90	<1	2	<1
Tin	ppm	ASTM D5185m >5	<1	2	0
Vanadium	ppm	ASTM D5185m	0	1	0
Cadmium	ppm	ASTM D5185m	0	2	0

ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m 0	2	11	10
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 60	62	55	59
Manganese	ppm	ASTM D5185m 0	<1	2	<1
Magnesium	ppm	ASTM D5185m 1010	1055	950	977
Calcium	ppm	ASTM D5185m 1070	1144	1087	1138
Phosphorus	ppm	ASTM D5185m 1150	1180	993	1036
Zinc	ppm	ASTM D5185m 1270	1461	1214	1275
Sulfur	ppm	ASTM D5185m 2060	3656	3693	3856

CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m >35	4	4	3
Sodium	ppm	ASTM D5185m	2	4	3
Potassium	ppm	ASTM D5185m >20	<1	6	3

INFRA-RED



method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844 >7.5	0.1	0.1	0.2
Nitration	Abs/cm	*ASTM D7624 >20	5.4	5.6	6.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	17.2	17.9	18.8

FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414 >25	13.2	13.5	15.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	8.8	9.3	8.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	14.1	13.9	13.8

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0075172 **Received** : 04 Oct 2023
Lab Number : **05968665** **Diagnosed** : 04 Oct 2023
Unique Number : 10675216 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 044 - Elizabeth City
 657 Old US 17
 Elizabeth City, NC
 US 27909
 Contact: TOM BAIRD
 tom.baird@gflenv.com
 T: (252)562-2645
 F: (252)264-4411

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)