


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**605567**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

Metal levels are typical for a new component breaking in.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	<b>PCA0105325</b>	PCA0100800	PCA0057123	
Sample Date	Client Info	<b>29 Sep 2023</b>	16 Aug 2023	24 Sep 2021	
Machine Age	mls	Client Info	<b>52205</b>	142508	3631
Oil Age	mls	Client Info	<b>52205</b>	142508	3631
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Changed	
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL	

### CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

### WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>60</b>	24	20
Chromium	ppm ASTM D5185m >20	<b>5</b>	3	1
Nickel	ppm ASTM D5185m >4	<b>&lt;1</b>	0	<1
Titanium	ppm ASTM D5185m	<b>4</b>	17	<1
Silver	ppm ASTM D5185m >3	<b>0</b>	0	<1
Aluminum	ppm ASTM D5185m >20	<b>27</b>	18	11
Lead	ppm ASTM D5185m >40	<b>0</b>	0	<1
Copper	ppm ASTM D5185m >330	<b>13</b>	14	48
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	4
Antimony	ppm ASTM D5185m	<b>---</b>	---	0
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

### ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	<b>&lt;1</b>	9	8
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 50	<b>61</b>	68	60
Manganese	ppm ASTM D5185m 0	<b>1</b>	0	<1
Magnesium	ppm ASTM D5185m 950	<b>983</b>	1078	886
Calcium	ppm ASTM D5185m 1050	<b>1412</b>	1584	1131
Phosphorus	ppm ASTM D5185m 995	<b>1069</b>	1213	892
Zinc	ppm ASTM D5185m 1180	<b>1387</b>	1672	1210
Sulfur	ppm ASTM D5185m 2600	<b>2747</b>	4731	2386

### CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>7</b>	3	2
Sodium	ppm ASTM D5185m	<b>4</b>	<1	2
Potassium	ppm ASTM D5185m >20	<b>26</b>	20	23



### INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>1.5</b>	0.7	0.5
Nitration	Abs/cm *ASTM D7624 >20	<b>11.3</b>	8.8	8.8
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>25.3</b>	21.6	21

### FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>20.3</b>	16.6	16.6
Base Number (BN)	mg KOH/g ASTM D2896	<b>4.8</b>	6.7	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.8	11.5

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0105325 **Received** : 04 Oct 2023  
**Lab Number** : 05968749 **Diagnosed** : 04 Oct 2023  
**Unique Number** : 10675300 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #118**  
 2196 BENNETT ROAD  
 PHILADELPHIA, PA  
 US 19116  
 Contact: ROSTY VITER  
 rviter@millertransgroup.com  
 T: (215)552-9832  
 F: (215)552-9892

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)