

OIL ANALYSIS REPORT

Sample Rating Trend


NORMAL



KEMP QUARRIES / HULBERT Machine Id WL131

Component
Rear Right Final Drive

MOBIL MOBILTRANS HD 50 (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0086851	PCA0061853	PCA0062109
Sample Date		Client Info		15 Sep 2023	29 Oct 2022	03 Jun 2022
Machine Age	hrs	Client Info		9868	8686	7704
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METAL	.S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>800	45	137	16
Chromium	ppm	ASTM D5185m	>10	0	<1	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m	>15	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>75	0	1	1
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>75	2	7	1
Tin	ppm	ASTM D5185m	>8	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		9	30	6
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		2	1	1
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		35	21	19
Calcium	ppm	ASTM D5185m		3200	3003	3181
Phosphorus	ppm	ASTM D5185m		1021	976	982
Zinc	ppm	ASTM D5185m		1250	1152	1202
Sulfur	ppm	ASTM D5185m		4606	6493	5540
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	13	13	12
Sodium	ppm	ASTM D5185m		1	0	0
Potassium	ppm	ASTM D5185m	>20	0	<1	1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2

Visc @ 40°C

cSt

ASTM D445 195


182

183

189



OIL ANALYSIS REPORT



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS Iron (ppm) Lead (ppm) 1400 25 1200 20 1000 E 15 800 600 400 200 Chromium (ppm) Aluminum (ppm) 25 20 E 15 Silicon (ppm) Copper (ppm) 200 100 150 600 틆 100 50 Viscosity @ 40°C Additives 3500 220 nhosnhorus 3000 200 (200 200 2500 E 2000 1500 1000 140 500 120



Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : MOB 1

: PCA0086851 : 05969919 : 10681869

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 04 Oct 2023 Diagnosed

: 05 Oct 2023 : Wes Davis Diagnostician

Kemp Quarries - Kemp Stone - Hulbert

17801 Hwy 80 Hulbert, OK US 74441

Contact:

hulbert@kempstone.com

T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)