




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**499M**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0093125</b>	GFL0055185	GFL0042331
Sample Date	Client Info		<b>11 Oct 2023</b>	18 Jul 2022	04 Feb 2022
Machine Age	hrs	Client Info	<b>20170</b>	4982	3761
Oil Age	hrs	Client Info	<b>4982</b>	3761	1762
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >90	<b>35</b>	74	▲ 109
Chromium	ppm	ASTM D5185m >20	<b>2</b>	3	5
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	1
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m >20	<b>5</b>	17	▲ 22
Lead	ppm	ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m >330	<b>2</b>	6	13
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	1	2
Antimony	ppm	ASTM D5185m	<b>---</b>	---	0
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>&lt;1</b>	8	3
Barium	ppm	ASTM D5185m 0	<b>12</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>62</b>	68	67
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	2
Magnesium	ppm	ASTM D5185m 1010	<b>990</b>	1001	1042
Calcium	ppm	ASTM D5185m 1070	<b>1099</b>	1214	1254
Phosphorus	ppm	ASTM D5185m 1150	<b>1043</b>	1105	1149
Zinc	ppm	ASTM D5185m 1270	<b>1295</b>	1369	1245
Sulfur	ppm	ASTM D5185m 2060	<b>2948</b>	3524	2230

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>9</b>	8	16
Sodium	ppm	ASTM D5185m	<b>5</b>	8	6
Potassium	ppm	ASTM D5185m >20	<b>6</b>	25	20

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	<b>0.6</b>	1.3	1.7
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.7</b>	14.6	16.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.0</b>	27.6	29.5

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.5</b>	26.0	29.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.0</b>	7.8	7.3







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.5</b>	15.1	14.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0093125 **Received** : 13 Oct 2023  
**Lab Number** : **05978692** **Diagnosed** : 16 Oct 2023  
**Unique Number** : 10695987 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 415 - Michigan East**  
 6200 Elmridge  
 Sterling Heights, MI  
 US 48313  
 Contact: Frank Wolak  
 fwolak@gflenv.com  
 T: (586)825-9514  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)