




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
834048
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0093705	GFL0087700	---
Sample Date	Client Info		12 Oct 2023	24 Aug 2023	---
Machine Age	hrs	Client Info	500	197	---
Oil Age	hrs	Client Info	0	0	---
Oil Changed	Client Info		Not Chngd	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	46	35	---
Chromium	ppm	ASTM D5185m >5	1	0	---
Nickel	ppm	ASTM D5185m >2	1	<1	---
Titanium	ppm	ASTM D5185m	<1	0	---
Silver	ppm	ASTM D5185m >3	<1	0	---
Aluminum	ppm	ASTM D5185m >30	5	3	---
Lead	ppm	ASTM D5185m >30	2	<1	---
Copper	ppm	ASTM D5185m >150	19	15	---
Tin	ppm	ASTM D5185m >5	2	<1	---
Vanadium	ppm	ASTM D5185m	<1	0	---
Cadmium	ppm	ASTM D5185m	<1	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	8	24	---
Barium	ppm	ASTM D5185m 0	8	0	---
Molybdenum	ppm	ASTM D5185m 60	51	45	---
Manganese	ppm	ASTM D5185m 0	14	12	---
Magnesium	ppm	ASTM D5185m 1010	726	764	---
Calcium	ppm	ASTM D5185m 1070	1132	1154	---
Phosphorus	ppm	ASTM D5185m 1150	613	695	---
Zinc	ppm	ASTM D5185m 1270	846	861	---
Sulfur	ppm	ASTM D5185m 2060	2039	2736	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	38	32	---
Sodium	ppm	ASTM D5185m	5	3	---
Potassium	ppm	ASTM D5185m >20	11	9	---

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0	0	---
Nitration	Abs/cm	*ASTM D7624 >20	11.7	9.3	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.8	19.7	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	20.6	17.9	---
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	4.2	7.2	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	LIGHT	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	LIGHT	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---
Free Water	scalar	*Visual		NEG	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	14.5	14.1	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0093705 **Received** : 16 Oct 2023
Lab Number : **05980263** **Diagnosed** : 18 Oct 2023
Unique Number : 10697558 **Diagnostician** : Angela Borella
Test Package : FLEET

GFL Environmental - 837 - Harrison TS
 22820 S State Route 291
 Harrisonville, MO
 US 64701
 Contact: BRYAN SWANSON
 bryanswanson@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: