


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**(89543X) Walgreens - Tractor**  
Machine Id  
**[Walgreens - Tractor] 136A67108**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0103697</b>	PCA0093640	---
Sample Date	Client Info		<b>02 Oct 2023</b>	11 May 2023	---
Machine Age	mls	Client Info	<b>624613</b>	612082	---
Oil Age	mls	Client Info	<b>12023</b>	0	---
Oil Changed	Client Info		<b>Changed</b>	Changed	---
Sample Status			<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	---
Glycol	WC Method		<b>NEG</b>	NEG	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>5</b>	9	---
Chromium	ppm	ASTM D5185m >4	<b>0</b>	<1	---
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	---
Titanium	ppm	ASTM D5185m	<b>26</b>	3	---
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m >25	<b>2</b>	<1	---
Lead	ppm	ASTM D5185m >45	<b>0</b>	0	---
Copper	ppm	ASTM D5185m >85	<b>0</b>	<1	---
Tin	ppm	ASTM D5185m >4	<b>0</b>	0	---
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>28</b>	8	---
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	---
Molybdenum	ppm	ASTM D5185m 50	<b>39</b>	56	---
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	---
Magnesium	ppm	ASTM D5185m 950	<b>778</b>	893	---
Calcium	ppm	ASTM D5185m 1050	<b>1286</b>	1189	---
Phosphorus	ppm	ASTM D5185m 995	<b>932</b>	1025	---
Zinc	ppm	ASTM D5185m 1180	<b>1234</b>	1222	---
Sulfur	ppm	ASTM D5185m 2600	<b>3515</b>	3784	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>5</b>	4	---
Sodium	ppm	ASTM D5185m	<b>1</b>	1	---
Potassium	ppm	ASTM D5185m >20	<b>3</b>	2	---



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.3</b>	0.4	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.6</b>	8.6	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.1</b>	18.9	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.0</b>	15.1	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>8.2</b>	8.0	---





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.9	11.4

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0103697     **Received** : 16 Oct 2023  
**Lab Number** : 05980315     **Diagnosed** : 17 Oct 2023  
**Unique Number** : 10697610     **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1365 - Berkeley-Nazareth**  
 6813 Chrisphalt Drive  
 Bath Borough, PA  
 US 18014  
 Contact: Stephen Mackes  
 smackes@transervice.com  
 T: (610)837-8103  
 F: (610)837-8105

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)