


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
125267
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0106325	PCA0098018	PCA0089696
Sample Date	Client Info		04 Oct 2023	08 Jun 2023	20 Jan 2023
Machine Age	mls Client Info		14251	11087	7122
Oil Age	mls Client Info		0	0	0
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m	>100	16	22	41
Chromium	ppm ASTM D5185m	>20	<1	<1	1
Nickel	ppm ASTM D5185m	>4	0	0	<1
Titanium	ppm ASTM D5185m		0	0	0
Silver	ppm ASTM D5185m	>3	0	0	0
Aluminum	ppm ASTM D5185m	>20	2	5	4
Lead	ppm ASTM D5185m	>40	<1	<1	4
Copper	ppm ASTM D5185m	>330	73	299	170
Tin	ppm ASTM D5185m	>15	<1	2	2
Vanadium	ppm ASTM D5185m		0	0	0
Cadmium	ppm ASTM D5185m		0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	2	3	15	33
Barium	ppm ASTM D5185m	0	0	0	0
Molybdenum	ppm ASTM D5185m	50	57	63	62
Manganese	ppm ASTM D5185m	0	<1	1	1
Magnesium	ppm ASTM D5185m	950	848	956	828
Calcium	ppm ASTM D5185m	1050	1030	1209	1286
Phosphorus	ppm ASTM D5185m	995	889	1100	1042
Zinc	ppm ASTM D5185m	1180	1084	1369	1260
Sulfur	ppm ASTM D5185m	2600	2577	3924	3633

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m	>25	6	8	17
Sodium	ppm ASTM D5185m		2	1	2
Potassium	ppm ASTM D5185m	>20	0	2	3



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	>3	0.3	0.3	0.3
Nitration	Abs/cm *ASTM D7624	>20	8.0	9.0	9.2
Sulfation	Abs/.1mm *ASTM D7415	>30	19.3	20.1	20.1

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414	>25	16.1	17.6	16.7
Base Number (BN)	mg KOH/g ASTM D2896		7.1	7.0	7.7









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	11.1

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0106325 **Received** : 17 Oct 2023
Lab Number : 05980917 **Diagnosed** : 17 Oct 2023
Unique Number : 10698212 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #119
 39 INDUSTRIAL AVE
 HASBROUCK HEIGHTS, NJ
 US 07604
 Contact: MIKE LONGETTE
 mlongette@millertransgroup.com
 T:
 F: (201)528-7053

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)