




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**810014**

Component  
**Natural Gas Engine**

Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0083138</b>	GFL0083127	GFL0083102
Sample Date	Client Info		<b>13 Oct 2023</b>	16 Aug 2023	31 Jul 2023
Machine Age	hrs	Client Info	<b>0</b>	0	0
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>N/A</b>	Changed	Not Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	<b>16</b>	10	7
Chromium	ppm	ASTM D5185m >4	<b>2</b>	<1	<1
Nickel	ppm	ASTM D5185m >2	<b>1</b>	0	<1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >9	<b>4</b>	3	2
Lead	ppm	ASTM D5185m >30	<b>3</b>	0	<1
Copper	ppm	ASTM D5185m >35	<b>3</b>	0	<1
Tin	ppm	ASTM D5185m >4	<b>2</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	<b>11</b>	11	14
Barium	ppm	ASTM D5185m 5	<b>10</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>87</b>	76	58
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m 560	<b>781</b>	692	521
Calcium	ppm	ASTM D5185m 1510	<b>2139</b>	1963	1521
Phosphorus	ppm	ASTM D5185m 780	<b>969</b>	786	673
Zinc	ppm	ASTM D5185m 870	<b>1289</b>	1224	910
Sulfur	ppm	ASTM D5185m 2040	<b>3597</b>	3858	2518

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	<b>6</b>	3	4
Sodium	ppm	ASTM D5185m	<b>25</b>	4	2
Potassium	ppm	ASTM D5185m >20	<b>3</b>	0	<1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	<b>0</b>	0	0
Nitration	Abs/cm	*ASTM D7624 >20	<b>11.9</b>	10.8	10.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>24.3</b>	21.0	19.6

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>19.7</b>	17.5	16.7
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	<b>3.3</b>	3.3	5.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.1	<b>14.1</b>	14.1	14.2

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0083138 **Received** : 17 Oct 2023  
**Lab Number** : **05981784** **Diagnosed** : 19 Oct 2023  
**Unique Number** : 10699079 **Diagnostician** : Don Baldrige  
**Test Package** : FLEET

**GFL Environmental - 074 - Douglas - Transwaste**  
 1219 Landfill Road  
 Douglas, GA  
 US 31533  
 Contact: CURTIS JACOBS  
 CURTIS.JACOBS@GFLENV.COM  
 T: (912)384-6001  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)