


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**AGCO MT845C AGCC0845KENHG1005**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON HP 15W40 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0096457</b>	PCA0081016	---
Sample Date	Client Info		<b>09 Oct 2023</b>	29 May 2023	---
Machine Age	hrs	Client Info	<b>4417</b>	4150	---
Oil Age	hrs	Client Info	<b>267</b>	260	---
Oil Changed	Client Info		<b>Changed</b>	Changed	---
Sample Status			<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	---
Glycol	WC Method		<b>NEG</b>	NEG	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>22</b>	23	---
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	---
Nickel	ppm	ASTM D5185m >4	<b>0</b>	<1	---
Titanium	ppm	ASTM D5185m	<b>0</b>	<1	---
Silver	ppm	ASTM D5185m >3	<b>0</b>	<1	---
Aluminum	ppm	ASTM D5185m >20	<b>1</b>	0	---
Lead	ppm	ASTM D5185m >40	<b>0</b>	5	---
Copper	ppm	ASTM D5185m >330	<b>2</b>	3	---
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	<1	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>5</b>	15	---
Barium	ppm	ASTM D5185m	<b>&lt;1</b>	4	---
Molybdenum	ppm	ASTM D5185m	<b>57</b>	68	---
Manganese	ppm	ASTM D5185m	<b>&lt;1</b>	1	---
Magnesium	ppm	ASTM D5185m	<b>939</b>	1036	---
Calcium	ppm	ASTM D5185m	<b>1005</b>	1195	---
Phosphorus	ppm	ASTM D5185m	<b>1000</b>	1067	---
Zinc	ppm	ASTM D5185m	<b>1215</b>	1330	---
Sulfur	ppm	ASTM D5185m	<b>2886</b>	3755	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	4	---
Sodium	ppm	ASTM D5185m	<b>&lt;1</b>	1	---
Potassium	ppm	ASTM D5185m >20	<b>&lt;1</b>	4	---



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.3</b>	0.2	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.3</b>	7.8	---
Sulfation	Abs.1mm	*ASTM D7415 >30	<b>19.7</b>	20.4	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs.1mm	*ASTM D7414 >25	<b>16.3</b>	17.8	---
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>9.84</b>	9.98	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.6	<b>12.9</b>	13.3	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0096457      **Received** : 18 Oct 2023  
**Lab Number** : **05982543**      **Diagnosed** : 19 Oct 2023  
**Unique Number** : 10699838      **Diagnostician** : Wes Davis  
**Test Package** : MOB 2

**VEENSTRA FARMING**  
 15861 SEXTON RD  
 ESCALON, CA  
 US 95320  
 Contact: DEREK VEENSTRA  
 KEREKVEENSTRA@AOL.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: