


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**302616**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0097324</b>	PCA0071736	PCA0061044
Sample Date	Client Info			<b>26 Jun 2023</b>	05 Jan 2023	21 Mar 2022
Machine Age	mls Client Info			<b>115460</b>	86788	49749
Oil Age	mls Client Info			<b>28674</b>	41973	4934
Oil Changed	Client Info			<b>Changed</b>	Changed	Not Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>34</b>	59	15
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	3	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>16</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>11</b>	21	6
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>330	<b>4</b>	8	2
Tin	ppm	ASTM D5185m	>15	<b>2</b>	4	<1
Antimony	ppm	ASTM D5185m		<b>---</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>8</b>	2	13
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	50	<b>53</b>	59	61
Manganese	ppm	ASTM D5185m	0	<b>1</b>	1	<1
Magnesium	ppm	ASTM D5185m	950	<b>868</b>	977	986
Calcium	ppm	ASTM D5185m	1050	<b>1186</b>	1254	1140
Phosphorus	ppm	ASTM D5185m	995	<b>1015</b>	936	1107
Zinc	ppm	ASTM D5185m	1180	<b>1233</b>	1196	1314
Sulfur	ppm	ASTM D5185m	2600	<b>3132</b>	3118	2828

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>6</b>	7	4
Sodium	ppm	ASTM D5185m		<b>5</b>	5	<1
Potassium	ppm	ASTM D5185m	>20	<b>9</b>	15	6

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.8</b>	1.1	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.5</b>	12.4	6.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.4</b>	24.7	19.0

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.9</b>	21.2	14.4
Base Number (BN)	mg KOH/g	ASTM D2896		<b>7.2</b>	6.4	10.3










# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.4</b>	11.2	11.3

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0097324 **Received** : 20 Oct 2023  
**Lab Number** : 05985390 **Diagnosed** : 23 Oct 2023  
**Unique Number** : 10702685 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #123**  
 66 KELLER AVENUE  
 LANCASTER, PA  
 US 17601  
 Contact: RON ROBERTS  
 roberts@millertransgroup.com  
 T: (717)945-6205  
 F: (717)945-5818

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)