


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **10858**

Component **Transmission (Auto)**

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition


The condition of the oil is acceptable for the time in service.

68 (GAL)		Sep 2022	Feb2023 Apr2023	May2023 Jun2023 S	ep2023	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0097861	GFL0094331	GFL0091400
Sample Date		Client Info		10 Oct 2023	15 Sep 2023	01 Sep 2023
Machine Age	hrs	Client Info		1370	1263	1121
Oil Age	hrs	Client Info		484	377	335
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR META	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	40	37	34
Chromium	ppm	ASTM D5185m	>5	<1	0	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	3	2	6
Lead	ppm	ASTM D5185m	>50	<1	0	0
Copper	ppm	ASTM D5185m	>225	5	3	5
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		50	48	46
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		2	3	2
Calcium	ppm	ASTM D5185m		124	126	128
Phosphorus	ppm	ASTM D5185m		212	91	217
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		1852	1955	1938
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	5	5
Sodium	ppm	ASTM D5185m		2	6	7
Potassium	ppm	ASTM D5185m	>20	2	0	<1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	ERTIES	method	limit/base	current	history1	history2
VI 0 4000	0.	4 OT14 D / / =	0.4		00.0	00.4

Visc @ 40°C




OIL ANALYSIS REPORT




SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image


GRAPHS



Non-ferrous Metals



Viscosity @ 40°C







Laboratory Sample No. Lab Number Unique Number : 10709702 Test Package : FLEET

: GFL0097861 : 05987040

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 23 Oct 2023 Received Diagnosed : 25 Oct 2023

Diagnostician : Sean Felton

GFL Environmental - 010 - Stockbridge 1280 Rum Creek Parkway

Stockbridge, GA US 30281

Contact: JOSHUA TINKER joshuatinker@gflenv.com

T: F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)