

# **OIL ANALYSIS REPORT**




## KEMP QUARRIES / NEOSHO [66108]

**WL146** Component

**Diesel Engine** 

PETRO CANADA DURON SHP 15W40 (--- GAL)





### **DIAGNOSIS**

#### Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor. ( Customer Sample Comment: PM-1 changed filters and fluid . Drained cold, antifreeze suspected)

#### Wear

The copper level is abnormal. Elemental level of copper (Cu) probably due to leaching of copper from copper components (i.e. cooling core) by the oil additives. All other component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

| SAMPLE INFORI                               | MATION                              | method   | limit/base            | current                                    | history1                                 | history2                                    |
|---|-------------------------------------|--|-----------------------|--|--|---|
| Sample Number                               |                                     | Client Info  |                       | PCA0084731                                 | PCA0085698                               | PCA0086749                                  |
| Sample Date                                 |                                     | Client Info  |                       | 10 Oct 2023                                | 18 May 2023                              | 17 Jan 2023                                 |
| Machine Age                                 | hrs                                 | Client Info  |                       | 25999                                      | 23565                                    | 25143                                       |
| Oil Age                                     | hrs                                 | Client Info  |                       | 25999                                      | 23565                                    | 25143                                       |
| Oil Changed                                 |                                     | Client Info  |                       | Changed                                    | Changed                                  | Changed                                     |
| Sample Status                               |                                     |  |                       | ABNORMAL                                   | ATTENTION                                | ATTENTION                                   |
| CONTAMINAT                                  | ION                                 | method   | limit/base            | current                                    | history1                                 | history2                                    |
| Fuel  |                                     | WC Method  | >5                    | <1.0                                       | <1.0                                     | <1.0  |
| WEAR METAL                                  | S                                   | method   | limit/base            | current                                    | history1                                 | history2                                    |
| Iron  | ppm                                 | ASTM D5185m  | >100                  | 70   | 50                                       | 72  |
| Chromium                                    | ppm                                 | ASTM D5185m  | >20                   | 1  | 1  | 1   |
| Nickel                                      | ppm                                 | ASTM D5185m  | >2                    | 1  | <1                                       | <1  |
| Titanium                                    | ppm                                 | ASTM D5185m  | >2                    | 0  | 0  | 0   |
| Silver                                      | ppm                                 | ASTM D5185m  | >2                    | 0  | 0  | 0   |
| Aluminum                                    | ppm                                 | ASTM D5185m  | >25                   | 1  | <1                                       | 0   |
| Lead  | ppm                                 | ASTM D5185m  | >40                   | 10   | 5  | 15  |
| Copper                                      | ppm                                 | ASTM D5185m  | >330                  | <u> </u>                                   | 144                                      | 41  |
| Tin   | ppm                                 | ASTM D5185m  | >15                   | <1   | 1  | 2   |
| Vanadium                                    | ppm                                 | ASTM D5185m  |                       | 0  | 0  | 0   |
| Cadmium                                     | ppm                                 | ASTM D5185m  |                       | 0  | 0  | 0   |
| ADDITIVES                                   |                                     | method   | limit/base            | current                                    | history1                                 | history2                                    |
| Boron                                       | ppm                                 | ASTM D5185m  | 0                     | 2  | 4  | 7   |
| Barium                                      | ppm                                 | ASTM D5185m  | 0                     | 0  | 0  | 0   |
| Molybdenum                                  | ppm                                 | ASTM D5185m  | 60                    | 65   | 71                                       | 68  |
| Manganese                                   | ppm                                 | ASTM D5185m  | 0                     | <1   | <1                                       | <1  |
| Magnesium                                   | ppm                                 | ASTM D5185m  | 1010                  | 973  | 970                                      | 927   |
| Calcium                                     | ppm                                 | ASTM D5185m  | 1070                  | 1060                                       | 1127                                     | 1131  |
| Phosphorus                                  | ppm                                 | ASTM D5185m  | 1150                  | 989  | 1079                                     | 1043  |
| Zinc  | ppm                                 | ASTM D5185m  | 1270                  | 1248                                       | 1321                                     | 1272  |
| Sulfur                                      | ppm                                 | ASTM D5185m  | 2060                  | 2524                                       | 3352                                     | 2748  |
| CONTAMINAN                                  | TS                                  | method   | limit/base            | current                                    | history1                                 | history2                                    |
| Silicon                                     | ppm                                 | ASTM D5185m  | >25                   | 6  | 5  | 8   |
| Sodium                                      |                                     |  |                       |  |  |   |
|   | ppm                                 | ASTM D5185m  |                       | 26   | <b>△</b> 66                              | <u>▲</u> 84                                 |
| Potassium                                   | ppm<br>ppm                          | ASTM D5185m<br>ASTM D5185m   | >20                   | 26<br>4                                    | <b>△</b> 66 5                            | ▲ 84<br>7                                   |
| Potassium<br>Glycol                         |                                     |  | >20                   | _  |  |   |
|   | ppm                                 | ASTM D5185m  | >20<br>limit/base     | 4  | 5  | 7   |
| Glycol                                      | ppm                                 | ASTM D5185m<br>*ASTM D2982   |                       | 4<br>NEG                                   | 5<br>NEG                                 | 7<br>NEG                                    |
| Glycol INFRA-RED                            | ppm<br>%                            | ASTM D5185m<br>*ASTM D2982<br>method                               | limit/base >3         | 4<br>NEG<br>current                        | 5<br>NEG<br>history1                     | 7<br>NEG<br>history2                        |
| Glycol INFRA-RED Soot %                     | ppm<br>%                            | ASTM D5185m<br>*ASTM D2982<br>method<br>*ASTM D7844                | limit/base >3         | 4 NEG current 1.6                          | 5<br>NEG<br>history1                     | 7<br>NEG<br>history2                        |
| Glycol  INFRA-RED  Soot %  Nitration        | ppm<br>%<br>%<br>Abs/cm<br>Abs/.1mm | ASTM D5185m *ASTM D2982 method *ASTM D7844 *ASTM D7624 *ASTM D7415 | limit/base >3 >20     | 4<br>NEG<br>current<br>1.6<br>11.5         | 5<br>NEG<br>history1<br>1<br>9.4         | 7<br>NEG<br>history2<br>1.6<br>12.5         |
| Glycol INFRA-RED Soot % Nitration Sulfation | ppm<br>%<br>%<br>Abs/cm<br>Abs/.1mm | ASTM D5185m *ASTM D2982 method *ASTM D7844 *ASTM D7624 *ASTM D7415 | limit/base >3 >20 >30 | 4<br>NEG<br>current<br>1.6<br>11.5<br>22.5 | 5<br>NEG<br>history1<br>1<br>9.4<br>22.0 | 7<br>NEG<br>history2<br>1.6<br>12.5<br>25.2 |



### **OIL ANALYSIS REPORT**





Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** 

: PCA0084731 : 05987154 : 10709816

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 25 Oct 2023 Diagnostician : Don Baldridge

: 23 Oct 2023

Test Package : MOB 1 (Additional Tests: Glycol, TBN) To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Kemp Quarries - Kemp Stone - Neosho

19148 Ingersol Lane Neosho, MO US 64850

Contact: neosho@kempstone.com

T:

F: