

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id DT632 Component **Transmission (Auto)**

COGNIS EMGARD 2805 ATF (42 mls)

DIAGNOSIS
Recommendation

Resample at the next service interval to monitor.

Fluic

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.


SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0103321	PCA0091167	PCA0080929
Sample Date		Client Info		27 Oct 2023	21 Apr 2023	27 Sep 2022
Machine Age	mls	Client Info		267491	242230	215908
Oil Age	mls	Client Info		267419	178348	152026
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	ABNORMAL	ABNORMAL
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>220	62	139	108
Chromium	ppm	ASTM D5185m	>2	0	<1	0
Nickel	ppm	ASTM D5185m	>5	<1	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>5	0	0	<1
Aluminum	ppm	ASTM D5185m	>75	23	47	34
Lead	ppm	ASTM D5185m	>95	14	31	32
Copper	ppm	ASTM D5185m	>60	46	4 95	▲ 77
Tin	ppm	ASTM D5185m	>10	3	4	4
Vanadium	ppm	ASTM D5185m		0	0	2
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		104	195	208
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		6	2	3
Manganese	ppm	ASTM D5185m		1	2	2
Magnesium	ppm	ASTM D5185m		67	19	9
Calcium	ppm	ASTM D5185m		203	168	165
Phosphorus	ppm	ASTM D5185m		369	457	506
Zinc	ppm	ASTM D5185m		92	55	26
Sulfur	ppm	ASTM D5185m		2398	2926	2917
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	6	6
Sodium	ppm	ASTM D5185m		6	8	9
Potassium	ppm	ASTM D5185m	>20	2	0	0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	35.2	34.5	34.9
8.01.21) Rov: 1			c	ubmitted By: Ur		Jamos Throatt

Report Id: NWWPIE [WUSCAR] 05994780 (Generated: 11/01/2023 18:01:24) Rev: 1

Submitted By: Under NWWDUN - James Threatt



OIL ANALYSIS REPORT



SAMPLE IMAGES method limit/	base current	history1	history2
Color	no image	no image	no image
Bottom	no image	no image	no image
Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC Sample No. : PCA0103321 Lab Number : 05994780 Unique Number : 10723140 Diagnostician : Don Baldright Test Package : FLEET a sample report, contact Customer Service at 1-800-237-1369. st methods that are outside of the ISO 17025 scope of accreditation. sonformity to specifications are based on the simple accentance decision	3 23 dge	F Contact: jthreatt T:	605 RIVER RD PIEDMONT, SC US 29673 James Threatt @nwwhite.com (864)918-4646 F

To discuss this sam * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

F: