

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id DT821
Component
Front Differential
Fluid

PETRO CANADA TRAXON SYNTHETIC 75W90 (4 GAL

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

| SYNTHETIC 75W90 | (4 GAL) | | | 0ct2023 | | |
|------------------|---------|-------------|------------|-------------|----------|----------|
| SAMPLE INFOR | RMATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PCA0103316 | | |
| Sample Date | | Client Info | | 26 Oct 2023 | | |
| Machine Age | mls | Client Info | | 40838 | | |
| Oil Age | mls | Client Info | | 40838 | | |
| Oil Changed | | Client Info | | Not Changd | | |
| Sample Status | | | | NORMAL | | |
| WEAR METAL | _S | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >870 | 39 | | |
| Chromium | ppm | ASTM D5185m | >8 | <1 | | |
| Nickel | ppm | ASTM D5185m | >25 | 2 | | |
| Titanium | ppm | ASTM D5185m | >4 | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >40 | 1 | | |
| Lead | ppm | ASTM D5185m | >25 | <1 | | |
| Copper | ppm | ASTM D5185m | >60 | <1 | | |
| Tin | ppm | ASTM D5185m | >5 | <1 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 328 | 154 | | |
| Barium | ppm | ASTM D5185m | 1 | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 14 | | |
| Manganese | ppm | ASTM D5185m | | 1 | | |
| Magnesium | ppm | ASTM D5185m | 1 | 128 | | |
| Calcium | ppm | ASTM D5185m | 7 | 228 | | |
| Phosphorus | ppm | ASTM D5185m | 1145 | 1136 | | |
| Zinc | ppm | ASTM D5185m | 3 | 195 | | |
| Sulfur | ppm | ASTM D5185m | 17909 | 18426 | | |
| CONTAMINAN | NTS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >285 | 34 | | |
| Sodium | ppm | ASTM D5185m | | 4 | | |
| Potassium | ppm | ASTM D5185m | >20 | 2 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >.2 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPE | ERTIES | method | limit/base | current | history1 | history2 |




OIL ANALYSIS REPORT




| SAMPLE IMAGE | S method | limit/base | current | history1 | history2 |
|--------------|----------|------------|----------|----------|----------|
| Color | | | no image | no image | no image |
| Bottom | | | no image | no image | no image |

GRAPHS



Non-ferrous Metals



Viscosity @ 40°C 135 T Abnormal 130 125 120 115 ⊕110 €105 90 85 80 75





Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10723165

: PCA0103316 : 05994805 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed Diagnostician : Don Baldridge

: 31 Oct 2023 : 02 Nov 2023 NW WHITE & CO - ANDERSON DIVISION 2605 RIVER RD PIEDMONT, SC

US 29673 Contact: James Threatt jthreatt@nwwhite.com

T: (864)918-4646

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: NWWPIE [WUSCAR] 05994805 (Generated: 11/02/2023 09:00:00) Rev: 1