


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
234008
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (9 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0106030	PCA0095319	PCA0098100
Sample Date	Client Info		23 Oct 2023	30 Aug 2023	23 Jun 2023
Machine Age	hrs	Client Info	1450	1056	484
Oil Age	hrs	Client Info	966	572	0
Oil Changed	Client Info		Changed	Not Changd	Not Changd
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	16	11	13
Chromium	ppm	ASTM D5185m >20	<1	<1	0
Nickel	ppm	ASTM D5185m >5	3	<1	4
Titanium	ppm	ASTM D5185m >2	0	0	0
Silver	ppm	ASTM D5185m >2	<1	<1	0
Aluminum	ppm	ASTM D5185m >20	2	4	0
Lead	ppm	ASTM D5185m >40	<1	<1	0
Copper	ppm	ASTM D5185m >330	103	1	10
Tin	ppm	ASTM D5185m >15	<1	<1	<1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	<1	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	1	<1	24
Barium	ppm	ASTM D5185m 0	4	4	0
Molybdenum	ppm	ASTM D5185m 60	66	63	60
Manganese	ppm	ASTM D5185m 0	<1	<1	<1
Magnesium	ppm	ASTM D5185m 1010	938	908	869
Calcium	ppm	ASTM D5185m 1070	1100	1062	1002
Phosphorus	ppm	ASTM D5185m 1150	1060	1075	886
Zinc	ppm	ASTM D5185m 1270	1211	1199	1087
Sulfur	ppm	ASTM D5185m 2060	2882	3285	3424

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	6	4	9
Sodium	ppm	ASTM D5185m	4	<1	5
Potassium	ppm	ASTM D5185m >20	3	10	<1



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	0.5	0.7	0.3
Nitration	Abs/cm	*ASTM D7624 >20	7.4	7.0	6.6
Sulfation	Abs.1mm	*ASTM D7415 >30	19.6	18.7	19.7

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs.1mm	*ASTM D7414 >25	15.3	13.7	16.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	7.9	9.2	8.6





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	14.0	13.6

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0106030 **Received** : 31 Oct 2023
Lab Number : **05994978** **Diagnosed** : 01 Nov 2023
Unique Number : 10723338 **Diagnostician** : Wes Davis
Test Package : FLEET

LRS - BETHEL HEIGHTS (NWA AR)
 848 HWY 264 E
 BETHEL HEIGHTS, AR
 US 72764
 Contact: JAMIE HAYWORTH
 jhayworth@lrsrecycles.com
 T: (479)878-1384
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)