




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
{UNASSIGNED}
Machine Id
413037
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 30 (24 QTS)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 30. Please confirm.

Wear

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0092706	GFL0072432	---
Sample Date	Client Info	26 Oct 2023	23 May 2023	---
Machine Age	hrs	627	0	---
Oil Age	hrs	627	679	---
Oil Changed	Client Info	Changed	Changed	---
Sample Status		NORMAL	ABNORMAL	---

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	0.3	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	39	46	---
Chromium	ppm ASTM D5185m >20	2	2	---
Nickel	ppm ASTM D5185m >5	3	6	---
Titanium	ppm ASTM D5185m >2	0	<1	---
Silver	ppm ASTM D5185m >2	0	<1	---
Aluminum	ppm ASTM D5185m >20	19	▲ 32	---
Lead	ppm ASTM D5185m >40	<1	2	---
Copper	ppm ASTM D5185m >330	50	195	---
Tin	ppm ASTM D5185m >15	2	5	---
Vanadium	ppm ASTM D5185m	0	<1	---
Cadmium	ppm ASTM D5185m	<1	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 250	6	78	---
Barium	ppm ASTM D5185m 10	<1	0	---
Molybdenum	ppm ASTM D5185m 100	74	111	---
Manganese	ppm ASTM D5185m	2	5	---
Magnesium	ppm ASTM D5185m 450	855	777	---
Calcium	ppm ASTM D5185m 3000	1209	1379	---
Phosphorus	ppm ASTM D5185m 1150	848	760	---
Zinc	ppm ASTM D5185m 1350	1136	944	---
Sulfur	ppm ASTM D5185m 4250	2496	2671	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	24	▲ 71	---
Sodium	ppm ASTM D5185m >75	0	4	---
Potassium	ppm ASTM D5185m >20	59	83	---

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	0.5	0.4	---
Nitration	Abs/cm *ASTM D7624 >20	10.2	11.0	---
Sulfation	Abs/.1mm *ASTM D7415 >30	22.6	24.4	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	20.5	24.6	---
Base Number (BN)	mg KOH/g ASTM D2896 8.5	5.0	6.4	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	10.9	12.5	10.6	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0092706 **Received** : 02 Nov 2023
Lab Number : **05996518** **Diagnosed** : 02 Nov 2023
Unique Number : 10724878 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 005 - Wilson/Tri-East (CNG)
 2810 Contentnea Road S
 Wilson, NC
 US 27893-8501
 Contact: SPENCER LIGGON
 spencer.liggon@gflenv.com
 T: (800)207-6618
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)