




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**827017-1028**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (11 LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0077806</b>	GFL0077822	GFL0065055
Sample Date	Client Info		<b>27 Oct 2023</b>	24 Jul 2023	25 Apr 2023
Machine Age	hrs	Client Info	<b>17755</b>	17162	16655
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	<b>20</b>	20	29
Chromium	ppm	ASTM D5185m >5	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m >2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m >15	<b>2</b>	1	2
Lead	ppm	ASTM D5185m >25	<b>6</b>	1	0
Copper	ppm	ASTM D5185m >100	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>7</b>	8	10
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>64</b>	66	60
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>993</b>	1036	996
Calcium	ppm	ASTM D5185m 1070	<b>1095</b>	1169	1187
Phosphorus	ppm	ASTM D5185m 1150	<b>1035</b>	1115	1023
Zinc	ppm	ASTM D5185m 1270	<b>1380</b>	1377	1271
Sulfur	ppm	ASTM D5185m 2060	<b>3093</b>	3812	3317

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>8</b>	8	10
Sodium	ppm	ASTM D5185m	<b>3</b>	5	4
Potassium	ppm	ASTM D5185m >20	<b>1</b>	<1	0

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	<b>0.5</b>	0.5	0.5
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.9</b>	9.2	8.4
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.6</b>	20.8	18.6

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.0</b>	16.6	15.5
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.4</b>	7.8	6.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.6	13.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0077806 **Received** : 03 Nov 2023  
**Lab Number** : **05998378** **Diagnosed** : 06 Nov 2023  
**Unique Number** : 10726738 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 650 - West Point Hauling**  
 7825 Parham Landing Road  
 West Point, VA  
 US 23181  
 Contact: Jason Smith  
 jasonsmith@gflenv.com  
 T:  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)