




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
721018-361460

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0088077	GFL0088236	GFL0067737
Sample Date	Client Info	24 Oct 2023	06 Oct 2023	18 Jul 2023
Machine Age	hrs	590	467	0
Oil Age	hrs	467	0	0
Oil Changed	Client Info	N/A	Changed	N/A
Sample Status		NORMAL	NORMAL	SEVERE

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	15	11	270
Chromium	ppm ASTM D5185m >20	2	<1	20
Nickel	ppm ASTM D5185m >4	<1	0	<1
Titanium	ppm ASTM D5185m	<1	0	<1
Silver	ppm ASTM D5185m >3	0	0	0
Aluminum	ppm ASTM D5185m >20	2	1	11
Lead	ppm ASTM D5185m >40	2	<1	14
Copper	ppm ASTM D5185m >330	<1	<1	4
Tin	ppm ASTM D5185m >15	2	0	3
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	36	39	2
Barium	ppm ASTM D5185m 0	4	0	0
Molybdenum	ppm ASTM D5185m 60	51	51	65
Manganese	ppm ASTM D5185m 0	2	<1	2
Magnesium	ppm ASTM D5185m 1010	835	741	980
Calcium	ppm ASTM D5185m 1070	1176	1098	1256
Phosphorus	ppm ASTM D5185m 1150	795	686	1084
Zinc	ppm ASTM D5185m 1270	979	848	1286
Sulfur	ppm ASTM D5185m 2060	2544	2220	2848

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	14	9	66
Sodium	ppm ASTM D5185m	18	10	3
Potassium	ppm ASTM D5185m >20	4	2	3

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.4	0.2	1.1
Nitration	Abs/cm *ASTM D7624 >20	8.3	6.3	12.8
Sulfation	Abs/.1mm *ASTM D7415 >30	20.7	19.3	25.1

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	17.2	15.6	23.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	8.7	8.8	8.5







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.1	14.2

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0088077 **Received** : 06 Nov 2023
Lab Number : 05999559 **Diagnosed** : 07 Nov 2023
Unique Number : 10727919 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 820 - Joplin Hauling
 3700 West 7th Street
 Joplin, MO
 US 64801
 Contact: James Jarrett
 jjarrett@gflenv.com
 T: (417)310-2802
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)