




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
834000

Component
Natural Gas Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0084641	GFL0084755	---
Sample Date	Client Info	01 Nov 2023	19 Jun 2023	---
Machine Age	hrs	Client Info	1216	35
Oil Age	hrs	Client Info	0	0
Oil Changed	Client Info	Changed	Not Changd	---
Sample Status		NORMAL	NORMAL	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	15	44
Chromium	ppm	ASTM D5185m >4	1	<1
Nickel	ppm	ASTM D5185m >2	<1	<1
Titanium	ppm	ASTM D5185m	0	0
Silver	ppm	ASTM D5185m >3	0	0
Aluminum	ppm	ASTM D5185m >9	14	30
Lead	ppm	ASTM D5185m >30	0	<1
Copper	ppm	ASTM D5185m >35	2	14
Tin	ppm	ASTM D5185m >4	<1	0
Vanadium	ppm	ASTM D5185m	0	0
Cadmium	ppm	ASTM D5185m	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	9	38
Barium	ppm	ASTM D5185m 0	0	2
Molybdenum	ppm	ASTM D5185m 60	56	47
Manganese	ppm	ASTM D5185m 0	2	15
Magnesium	ppm	ASTM D5185m 1010	692	786
Calcium	ppm	ASTM D5185m 1070	1618	1101
Phosphorus	ppm	ASTM D5185m 1150	765	755
Zinc	ppm	ASTM D5185m 1270	1109	897
Sulfur	ppm	ASTM D5185m 2060	2784	2912

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	8	37
Sodium	ppm	ASTM D5185m	6	8
Potassium	ppm	ASTM D5185m >20	56	90

INFRA-RED




method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0.1
Nitration	Abs/cm	*ASTM D7624 >20	11.0	7.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.8	20.6

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	18.4	17.5
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	4.6	9.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	15.0	13.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0084641 **Received** : 06 Nov 2023
Lab Number : **05999638** **Diagnosed** : 07 Nov 2023
Unique Number : 10727998 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 856 - Houston South
 8515 Highway 6 South
 Houston, TX
 US 77083
 Contact: Apolinar Zacarias
 pzacariascano@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)