


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
KENWORTH 26

Component
Diesel Engine

Fluid
PETRO CANADA DURON XL SYN BLEND 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0105044	PCA0054216	PCA0053873
Sample Date	Client Info		18 Oct 2023	26 Jun 2023	06 Aug 2021
Machine Age	mls	Client Info	61823	46544	298227
Oil Age	mls	Client Info	20000	20000	20000
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	8	62	36
Chromium	ppm	ASTM D5185m >20	<1	2	3
Nickel	ppm	ASTM D5185m >4	0	1	0
Titanium	ppm	ASTM D5185m	0	<1	<1
Silver	ppm	ASTM D5185m >3	0	<1	<1
Aluminum	ppm	ASTM D5185m >20	3	15	3
Lead	ppm	ASTM D5185m >40	0	3	4
Copper	ppm	ASTM D5185m >330	2	16	2
Tin	ppm	ASTM D5185m >15	<1	4	<1
Antimony	ppm	ASTM D5185m	---	---	0
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 1	4	257	11
Barium	ppm	ASTM D5185m 1	0	4	0
Molybdenum	ppm	ASTM D5185m 60	60	87	64
Manganese	ppm	ASTM D5185m 1	<1	6	<1
Magnesium	ppm	ASTM D5185m 1010	983	447	987
Calcium	ppm	ASTM D5185m 1070	1083	1453	1252
Phosphorus	ppm	ASTM D5185m 1150	1106	1027	1120
Zinc	ppm	ASTM D5185m 1270	1311	1305	1220
Sulfur	ppm	ASTM D5185m 2060	3125	3707	2490

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	10	50	14
Sodium	ppm	ASTM D5185m	<1	5	2
Potassium	ppm	ASTM D5185m >20	0	53	3



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.2	0.6	1.1
Nitration	Abs/cm	*ASTM D7624 >20	8.9	8.6	12.4
Sulfation	Abs/.1mm	*ASTM D7415 >30	20.7	23.8	24.3

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	19.2	19.3	19
Base Number (BN)	mg KOH/g	ASTM D2896 9.6	7.1	6.07	9.71









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.5	13.1	13.0	13.7

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0105044 **Received** : 06 Nov 2023
Lab Number : 05999719 **Diagnosed** : 07 Nov 2023
Unique Number : 10728079 **Diagnostician** : Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

B & B HARVESTING
 2842 LADD RD
 MODESTO, CA
 US 95356
 Contact: Service Manager
 drcalvalley@gmail.com
 T: (209)545-8300
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)