


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



COMP 18 (S/N 160172)

Refrigeration Compressor

CAMCO 717 SC (45 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2021	Jan 2022	Jul2022 Dec2022	Nov2023	
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0109514	PCA0080239	PCA0078698
Sample Date		Client Info		08 Nov 2023	12 Dec 2022	20 Jul 2022
Machine Age	hrs	Client Info		28885	24829	23416
Oil Age	hrs	Client Info		28885	24829	23416
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS	;	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	0	0	0
Chromium	ppm	ASTM D5185m	>2	<1	0	0
Nickel	ppm	ASTM D5185m		<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>3	2	0	0
Lead	ppm	ASTM D5185m	>2	<1	0	0
Copper	ppm	ASTM D5185m	>8	<1	0	0
Tin	ppm	ASTM D5185m	>4	<1	0	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
	ppm	ASTM D5185m		0	0	0
	ppm	ASTM D5185m		0	<1	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		3	38	7
Zinc	ppm	ASTM D5185m		0	6	0
	ppm	ASTM D5185m		0	0	9
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	1
	ppm	ASTM D5185m		0	<1	0
	ppm	ASTM D5185m	>20	<1	0	0
	%	ASTM D6304	>0.01	0.001	0.003	0.002
	ppm	ASTM D6304	>100	12.8	32.9	21.3
FLUID CLEANLI	INESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>10000	1872	681	288
Particles >6µm		ASTM D7647	>2500	383	244	52
Particles >14µm		ASTM D7647	>640	14	21	5
Particles >21µm		ASTM D7647	>160	2	5	1
Particles >38µm		ASTM D7647	>40	0	0	0
Particles >71µm		ASTM D7647	>10	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/16	18/16/11	17/15/12	15/13/10
	A T1034					
FLUID DEGRAD	ATION	method				history2

Acid Number (AN)

mg KOH/g ASTM D974

0.014 0.014 Contact/Location: RYAN SCHMID - KRANEW



OIL ANALYSIS REPORT

