


# OIL ANALYSIS REPORT



Area  
**KEMP QUARRIES / PRYOR STONE [65429]**  
Machine Id  
**OHT066**  
Component  
**Transmission (Manual)**  
Fluid  
**PETRO CANADA PRODURO TO-4 SAE 30 (--- GAL)**

## Sample Rating Trend



**NORMAL**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: Pm3 performed. All oil samples taken. Engine oil, and all filters changed. )

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.

### Fluid Condition

The condition of the fluid is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0084307</b>	PCA0084015	PCA0070311
Sample Date	Client Info		<b>02 Nov 2023</b>	22 May 2023	30 Dec 2022
Machine Age	hrs	Client Info	<b>63909</b>	63506	62973
Oil Age	hrs	Client Info	<b>403</b>	1074	62432
Oil Changed	Client Info		<b>Oil Added</b>	Changed	Oil Added
Sample Status			<b>NORMAL</b>	ATTENTION	NORMAL

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >200	<b>4</b>	2	5
Chromium	ppm	ASTM D5185m >5	<b>0</b>	0	0
Nickel	ppm	ASTM D5185m >5	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >7	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>2</b>	0	2
Lead	ppm	ASTM D5185m >45	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m >225	<b>2</b>	2	4
Tin	ppm	ASTM D5185m >10	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>9</b>	0	0
Barium	ppm	ASTM D5185m 0	<b>0</b>	2	0
Molybdenum	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Manganese	ppm	ASTM D5185m 9	<b>0</b>	0	0
Magnesium	ppm	ASTM D5185m 1	<b>11</b>	2	8
Calcium	ppm	ASTM D5185m 3131	<b>1865</b>	▲ 447	1574
Phosphorus	ppm	ASTM D5185m 1194	<b>657</b>	▲ 417	631
Zinc	ppm	ASTM D5185m 1281	<b>786</b>	▲ 538	765
Sulfur	ppm	ASTM D5185m 3811	<b>2294</b>	▲ 1536	3002

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >125	<b>15</b>	4	9
Sodium	ppm	ASTM D5185m	<b>&lt;1</b>	0	1
Potassium	ppm	ASTM D5185m >20	<b>0</b>	<1	0


## VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual >0.1	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual	<b>NEG</b>	NEG	NEG

## FLUID PROPERTIES









	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 88.5	<b>77.1</b>	72.4	88.7

# OIL ANALYSIS REPORT



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0084307  
**Lab Number** : 06006612  
**Unique Number** : 10740374  
**Test Package** : MOB 1

**Kemp Quarries - Pryor Stone - Pryor**  
 1050 E 520 Rd  
 Pryor, OK  
 US 74361  
 Contact:  
 pryor@pryorstone.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: