


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



Machine Id T313 Component

Transmission (Auto)

DEXRON III (--- GAL)

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the

### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

		Ap	r2023	Jul2023 Nov20	23	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0107462	PCA0100088	PCA009564
Sample Date		Client Info		10 Nov 2023	29 Jul 2023	11 Apr 2023
Machine Age	mls	Client Info		282685	256404	229406
Oil Age	mls	Client Info		30000	229406	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METAL	_S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	41	33	25
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m		10	10	7
Lead	ppm	ASTM D5185m	>50	26	24	15
Copper	ppm	ASTM D5185m		59	41	16
Tin		ASTM D5185m	>10	<1	2	<1
Vanadium	ppm	ASTM D5185m	>10	0	0	0
	ppm			-		
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		119	164	136
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		0	1	0
Calcium	ppm	ASTM D5185m		124	148	133
Phosphorus	ppm	ASTM D5185m		299	313	334
Zinc	ppm	ASTM D5185m		26	27	10
Sulfur	ppm	ASTM D5185m		2141	2436	2827
CONTAMINAN	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	3	4	3
Sodium	ppm	ASTM D5185m		5	3	4
Potassium	ppm	ASTM D5185m	>20	0	<1	<1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual	2011	NEG	NEG	NEG
FLUID PROPE		method	limit/base	current	history1	history2
		motiloa	- mm/basc	Garrone		HISTORY Z

Visc @ 40°C

cSt


ASTM D445 35.0

31.9

33.2




## **OIL ANALYSIS REPORT**







#### **GRAPHS**



#### Non-ferrous Metals



### Viscosity @ 40°C







Laboratory Sample No. Lab Number Unique Number : 10741063 Test Package : FLEET

: PCA0107462 : 06007301

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 14 Nov 2023 Diagnosed : 16 Nov 2023

Diagnostician : Sean Felton

NW WHITE & CO - COLUMBIA DIVISION

100 INDEPENDENCE BLVD COLUMBIA, SC US 29210

Contact: GEORGE EDWARDS

gedwards@nwwhite.com

T:

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: NWWCOL [WUSCAR] 06007301 (Generated: 11/16/2023 22:48:07) Rev: 1

Submitted By: Paul Riddick

F: