OIL DIAGNOSTICS

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL

Area
(AU760S) Supermarket - Tractor
Machine Id
FREIGHTLINER 107A8818
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation
Resample at the next service interval to monitor.

Wear
Metal levels are typical for a new component breaking in.

Contamination
There is no indication of any contamination in the oil.

Fluid Condition
The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		**PCA0110994**	PCA0099848	---
Sample Date		Client Info		**03 Nov 2023**	24 Jul 2023	---
Machine Age	mls	Client Info		**32983**	32980	---
Oil Age	mls	Client Info		**3**	17	---
Oil Changed		Client Info		**Not Changd**	Not Changd	---
Sample Status				**NORMAL**	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel		WC Method	>5	**<1.0**	<1.0	---
Glycol		WC Method		**NEG**	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	**2**	2	---
Chromium	ppm	ASTM D5185m	>5	**<1**	0	---
Nickel	ppm	ASTM D5185m	>2	**0**	0	---
Titanium	ppm	ASTM D5185m		**<1**	0	---
Silver	ppm	ASTM D5185m	>3	**0**	0	---
Aluminum	ppm	ASTM D5185m	>30	**1**	<1	---
Lead	ppm	ASTM D5185m	>30	**0**	0	---
Copper	ppm	ASTM D5185m	>150	**5**	1	---
Tin	ppm	ASTM D5185m	>5	**0**	0	---
Vanadium	ppm	ASTM D5185m		**<1**	0	---
Cadmium	ppm	ASTM D5185m		**0**	0	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	**14**	18	---
Barium	ppm	ASTM D5185m	0	**0**	1	---
Molybdenum	ppm	ASTM D5185m	50	**59**	69	---
Manganese	ppm	ASTM D5185m	0	**<1**	<1	---
Magnesium	ppm	ASTM D5185m	950	**861**	1044	---
Calcium	ppm	ASTM D5185m	1050	**999**	1186	---
Phosphorus	ppm	ASTM D5185m	995	**935**	1151	---
Zinc	ppm	ASTM D5185m	1180	**1193**	1373	---
Sulfur	ppm	ASTM D5185m	2600	**2775**	4183	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	**4**	4	---
Sodium	ppm	ASTM D5185m		**2**	2	---
Potassium	ppm	ASTM D5185m	>20	**2**	<1	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	**0**	0	---
Nitration	Abs/cm	*ASTM D7624	>20	**4.4**	4.4	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	**16.8**	16.7	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	**12.4**	12.5	---
Base Number (BN)	mg KOH/g	ASTM D2896		**8.5**	9.4	---

OIL ANALYSIS REPORT

Base Number



Viscosity @ 100°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	**NONE**	NONE	---
Yellow Metal	scalar	*Visual	NONE	**NONE**	NONE	---
Precipitate	scalar	*Visual	NONE	**NONE**	NONE	---
Silt	scalar	*Visual	NONE	**NONE**	NONE	---
Debris	scalar	*Visual	NONE	**NONE**	NONE	---
Sand/Dirt	scalar	*Visual	NONE	**NONE**	NONE	---
Appearance	scalar	*Visual	NORML	**NORML**	NORML	---
Odor	scalar	*Visual	NORML	**NORML**	NORML	---
Emulsified Water	scalar	*Visual	>0.2	**NEG**	NEG	---
Free Water	scalar	*Visual		**NEG**	NEG	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	**11.3**	11.4	---

GRAPHS

Ferrous Alloys



Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0110994
Lab Number : 06010536
Unique Number : 10749680
Test Package : FLEET

Received : 17 Nov 2023
Diagnosed : 17 Nov 2023
Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-237-1369.
** - Denotes test methods that are outside of the ISO 17025 scope of accreditation.*
Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Transervice - Shop 1071 - Supermarket-Dayton
60 A Tower Road
Dayton, NJ
US 08810
Contact: Brian Quinn
bquinn@transervice.com
T:
F:

Report Id: TSV1071 [WUSCAR] 06010536 (Generated: 11/17/2023 16:35:34) Rev: 1

Submitted By: Brian Quinn