




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**913063**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (33 QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0059267</b>	GFL0059129	GFL0084975
Sample Date	Client Info		<b>15 Nov 2023</b>	23 Oct 2023	04 Oct 2023
Machine Age	mls	Client Info	<b>17006</b>	15731	14813
Oil Age	mls	Client Info	<b>11556</b>	11199	142
Oil Changed	Client Info		<b>N/A</b>	N/A	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>63</b>	3	85
Chromium	ppm	ASTM D5185m >20	<b>2</b>	0	3
Nickel	ppm	ASTM D5185m >5	<b>5</b>	0	1
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	1	4
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	6
Copper	ppm	ASTM D5185m >330	<b>14</b>	0	2
Tin	ppm	ASTM D5185m >15	<b>2</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	4
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	55	63
Manganese	ppm	ASTM D5185m 0	<b>1</b>	0	1
Magnesium	ppm	ASTM D5185m 1010	<b>878</b>	895	972
Calcium	ppm	ASTM D5185m 1070	<b>1033</b>	1034	1112
Phosphorus	ppm	ASTM D5185m 1150	<b>905</b>	949	1082
Zinc	ppm	ASTM D5185m 1270	<b>1200</b>	1177	1341
Sulfur	ppm	ASTM D5185m 2060	<b>1804</b>	2753	2829

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>6</b>	9	10
Sodium	ppm	ASTM D5185m	<b>7</b>	4	34
Potassium	ppm	ASTM D5185m >20	<b>2</b>	1	4

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>1.3</b>	0.1	1.5
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.9</b>	5.8	15.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>23.7</b>	17.8	27.7

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>21.5</b>	13.8	29.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>5.2</b>	8.5	7.1







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.5</b>	13.6	15.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0059267 **Received** : 17 Nov 2023  
**Lab Number** : **06010551** **Diagnosed** : 17 Nov 2023  
**Unique Number** : 10749695 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 410 - Michigan West**  
 39000 Van Born Rd  
 Wayne, MI  
 US 48184  
 Contact: Belal Dgheish  
 bdgheish@gflenv.com  
 T: (734)714-2340  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)