




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**912019**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (36 QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0059270</b>	GFL0059140	GFL0059173
Sample Date	Client Info		<b>15 Nov 2023</b>	07 Nov 2023	03 Nov 2023
Machine Age	hrs	Client Info	<b>3601</b>	3601	3601
Oil Age	hrs	Client Info	<b>3601</b>	0	3601
Oil Changed		Client Info	<b>N/A</b>	Changed	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>60</b>	25	26
Chromium	ppm	ASTM D5185m >20	<b>2</b>	3	1
Nickel	ppm	ASTM D5185m >5	<b>5</b>	<1	0
Titanium	ppm	ASTM D5185m >2	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	31	7
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	<1	0
Copper	ppm	ASTM D5185m >330	<b>13</b>	7	2
Tin	ppm	ASTM D5185m >15	<b>2</b>	<1	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>3</b>	<1	6
Barium	ppm	ASTM D5185m 0	<b>0</b>	6	0
Molybdenum	ppm	ASTM D5185m 60	<b>63</b>	62	65
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>947</b>	883	1033
Calcium	ppm	ASTM D5185m 1070	<b>1078</b>	1082	1163
Phosphorus	ppm	ASTM D5185m 1150	<b>1017</b>	988	1050
Zinc	ppm	ASTM D5185m 1270	<b>1292</b>	1177	1409
Sulfur	ppm	ASTM D5185m 2060	<b>2219</b>	3346	2974

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>7</b>	10	6
Sodium	ppm	ASTM D5185m	<b>5</b>	42	1
Potassium	ppm	ASTM D5185m >20	<b>1</b>	59	1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>1.3</b>	0.7	1.5
Nitration	Abs./cm	*ASTM D7624 >20	<b>11.1</b>	7.7	12.9
Sulfation	Abs./1mm	*ASTM D7415 >30	<b>23.5</b>	19.3	24.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs./1mm	*ASTM D7414 >25	<b>21.8</b>	14.5	21.9
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>4.7</b>	8.6	8.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	14.5

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0059270 **Received** : 17 Nov 2023  
**Lab Number** : **06010555** **Diagnosed** : 20 Nov 2023  
**Unique Number** : 10749699 **Diagnostician** : Sean Felton  
**Test Package** : FLEET

**GFL Environmental - 410 - Michigan West**  
 39000 Van Born Rd  
 Wayne, MI  
 US 48184  
 Contact: Belal Dgheish  
 bdgheish@gflenv.com  
 T: (734)714-2340  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)